

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

- Trade name: **Acrylic Spray Filler**
- Article number: 90051
- UFI: 69W7-60R7-D006-QYAF

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Filler and surfacer

#### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg
- Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

#### Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER/doctor if you feel unwell.

#### Storage:

Store in a well-ventilated place. Keep cool.  
Store in a well-ventilated place. Keep container tightly closed.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

##### Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

#### Signal word

Danger

#### Hazard-determining components of labelling:

reaction mass of ethylbenzole and xylene

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 1)

· <u>Precautionary statements</u>	<p>H319 Causes serious eye irritation.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P103 Read carefully and follow all instructions.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P260 Do not breathe spray.</p> <p>P280 Wear protective gloves / eye protection.</p> <p>P284 [In case of inadequate ventilation] wear respiratory protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.</p> <p>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
· <u>Additional information:</u>	<p>Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.</p> <p>Buildup of explosive mixtures possible without sufficient ventilation.</p> <p>Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</p>
· <b>2.3 Other hazards</b>	
· <u>Results of PBT and vPvB assessment</u>	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.
· <u>Determination of endocrine-disrupting properties</u>	For information on endocrine disrupting properties see section 11.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-50%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	12.5-25%

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 2)

CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<10%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · **4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Take affected persons out into the fresh air. Position and transport stably in side position.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

#### · **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty  
 Headache  
 Dizziness  
 Dizziness  
 Nausea  
 Danger of impaired breathing.

#### · Hazards

#### · **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.  
 If swallowed or in case of vomiting, danger of entering the lungs.

### SECTION 5: Firefighting measures

#### · **5.1 Extinguishing media**

- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

#### · For safety reasons unsuitable extinguishing agents:

Water with full jet

#### · **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:  
 Carbon monoxide (CO)  
 Formation of toxic gases is possible during heating or in case of fire.

#### · **5.3 Advice for firefighters**

- Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name:** Acrylic Spray Filler

(Contd. of page 3)

Do not inhale explosion gases or combustion gases.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Mount respiratory protective device.

- **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of the material collected according to regulations.  
Do not flush with water or aqueous cleansing agents  
Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

- **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:**

Not required.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.  
Keep container tightly sealed.  
Do not seal receptacle gas tight.  
Protect from heat and direct sunlight.

- **Storage class:**

2 B

- **7.3 Specific end use(s)**

No further relevant information available.

(Contd. on page 5)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**reaction mass of ethylbenzole and xylene**

AGW	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm H
-----	---

**67-64-1 acetone**

IOELV	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-------	---

· DNELs**reaction mass of ethylbenzole and xylene**

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	180-212 mg/kg bw/day (ARB)
		108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-442 mg/m <sup>3</sup> Air (ARB)
		260 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	211-221 mg/m <sup>3</sup> Air (ARB) 14.8-65.3 mg/m <sup>3</sup> Air (BEV)

**67-64-1 acetone**

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	186 mg/kg bw/day (ARB)
		62 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	1,210 mg/m <sup>3</sup> Air (ARB) 200 mg/m <sup>3</sup> Air (BEV)

· PNECs**reaction mass of ethylbenzole and xylene**

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
	0.327 mg/l (WAS)
PNEC (fest)	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

**67-64-1 acetone**

PNEC (wässrig)	100 mg/l (KA)
	1.06 mg/l (MW)
	10.6 mg/l (SW)
	21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO)
	3.04 mg/kg Trockengew (MWS)
	30.4 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls**· Appropriate engineering controls No further data; see section 7.

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31


Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

#### Trade name: Acrylic Spray Filler

(Contd. of page 5)

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes and skin.
  - Do not inhale gases / fumes / aerosols.
  - Do not eat, drink, smoke or sniff while working.
  - Use skin protection cream for skin protection.
  - Clean skin thoroughly immediately after handling the product.
- Respiratory protection:
  - Not necessary if room is well-ventilated.
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - Filter AX
- Hand protection
  -  Protective gloves
  - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
  - Preventive skin protection by use of skin-protecting agents is recommended.
  - After use of gloves apply skin-cleaning agents and skin cosmetics.
  - The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.
  - The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
  - This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
- Material of gloves
  - Butyl rubber, BR
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - Value for the permeation: Level ≤ 1, 20 min
- For the permanent contact gloves made of the following materials are suitable:
  - Butyl rubber, BR
  - Butoject (KCL, Art\_No. 897, 898)
- As protection from splashes gloves made of the following materials are suitable:
  - Butyl rubber, BR
  - Butoject (KCL, Art\_No. 897, 898)
- Not suitable are gloves made of the following materials:
  - Neoprene gloves
  - Nitrile rubber, NBR
  - Leather gloves
  - Strong material gloves

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 6)

· Eye/face protection

Tightly sealed goggles

· Body protection:

Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**· General Information

· <u>Colour:</u>	According to product specification
· <u>Odour:</u>	Specific type
· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	Not applicable, as aerosol.
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	1 Vol % (106-97-8 butane, pure)
· <u>Upper:</u>	10.9 Vol % (74-98-6 propane)
· <u>Flash point:</u>	Not applicable, as aerosol.
· <u>Auto-ignition temperature:</u>	365 °C (106-97-8 butane, pure)
· <u>pH</u>	Not determined.
	Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	8,300 hPa (74-98-6 propane)
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.7 g/cm <sup>3</sup>

**9.2 Other information**

· <u>Appearance:</u>	
· <u>Form:</u>	Aerosol
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	In use, may form flammable/explosive vapour-air mixture.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	79.3 %
· <u>Solids content:</u>	13.6 %

· Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void

(Contd. on page 8)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name:** Acrylic Spray Filler

(Contd. of page 7)

· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**74-98-6 propane**

Inhalative LC50/4 h &gt;20 mg/l (rat)

**106-97-8 butane, pure**

Inhalative LC50/4 h 658 mg/l (rat)

**reaction mass of ethylbenzole and xylene**

Oral	LD50	3,523 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat)
Dermal	LD50	12,126 mg/kg (rabbit)
	Inhalative	LC50/4h 29,000 mg/m <sup>3</sup> (rat)
Inhalative	LC50/4 h	27.124 mg/l (rat)

**75-28-5 isobutane**

Inhalative LC50/4 h &gt;50 mg/l (rat)

**67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat)
		7,426-15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)
	NOAEL	22,500 mg/m <sup>3</sup> (rat)
	LC50/48h	8,450 mg/l (crustaceans) 2,262 mg/l (daphnia magna)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 8)

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information**· **12.1 Toxicity**· Aquatic toxicity:**reaction mass of ethylbenzole and xylene**

LC50/24h	1 mg/l (daphnia magna) (OECD 202)
EC50/48h	3.2-9.5 mg/l (daphnia magna) (US EPA)
ErC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC	16 mg/l (BES) 1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (algae)
NOEC/21d	1.57 mg/l (daphnia magna) (OECD 211)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	1-10 mg/l (algae) 2.2 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	1-10 mg/l (fish) 86 mg/l (Leuciscus idus) 2.6 mg/l (Oncorhynchus mykiss) (OECD 203) 8.9-16.4 mg/l (pimephales promelas)

**67-64-1 acetone**

EC50/96h	7,200 mg/l (algae) 8,300 mg/l (piscis) 8,300 mg/l (lepomis macrochirus) 7,500 mg/l (selenastrum capricornutum)
EC50	1,700 mg/l (bacteria)
LC50	6,368 mg/l (piscis)
LC50/24h	8,800 mg/l (daphnia)
EC5/16h	1,700 mg/l (pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (microorganisms)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
EC50/48h	3,400 mg/l (algae) 8,800 mg/l (daphnia magna)
NOEC	1,700 mg/kg (pseudomonas putida) 4,740 mg/kg (selenastrum capricornutum)
NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.) 8,800 mg/l (daphnia magna)
LC50/96h	8,300 mg/l (lem)

(Contd. on page 10)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name:** Acrylic Spray Filler

(Contd. of page 9)

8,300 mg/l (Iepomis macrochirus)
7,500 mg/l (Leuciscus idus)
5,540 mg/l (Oncorhynchus mykiss)
8,120 mg/l (Pimephales promelas)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· PBT:

Not applicable.

· vPvB:

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents:

Alcohol

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· ADR, IMDG, IATA

UN1950

(Contd. on page 11)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name:** Acrylic Spray Filler

(Contd. of page 10)

**· 14.2 UN proper shipping name**

· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable

**· 14.3 Transport hazard class(es)**

· ADR



· Class	2.1 Gases.
· Label	2.1

· IMDG, IATA



· Class	2.1 Gases.
· Label	2.1

**· 14.4 Packing group**

· ADR, IMDG, IATA	Void
-------------------	------

**· 14.5 Environmental hazards:**

· Marine pollutant:	No
---------------------	----

**· 14.6 Special precautions for user**

· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

**· 14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D

(Contd. on page 12)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 11)

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 | acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 | acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 | acetone

3

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 604.4 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

(Contd. on page 13)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.02.2024

Version number 10 (replaces version 9)

Revision: 19.02.2024

**Trade name: Acrylic Spray Filler**

(Contd. of page 12)

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

<ul style="list-style-type: none"> <li>· <u>Department issuing SDS:</u></li> <li>· <u>Date of previous version:</u></li> <li>· <u>Version number of previous version:</u></li> <li>· <u>Abbreviations and acronyms:</u></li> </ul>	<p>Laboratory 07.11.2022 9</p> <p>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative ATE: Acute toxicity estimate values Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1</p>
--	---

EU