

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

- Trade name: **Akepox 2040 Component B**
- Article number: 10651 ( 10611), 10652 ( 10606), 11624 (11626), 11625 ( 11628), 10653 (10622)
- UFI: KQK5-3034-X00G-18AN

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy resin adhesive

#### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg
- Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

#### Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

- Acute Tox. 4      H332 Harmful if inhaled.
- Skin Corr. 1B      H314 Causes severe skin burns and eye damage.
- Eye Dam. 1      H318 Causes serious eye damage.
- Skin Sens. 1      H317 May cause an allergic skin reaction.
- Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

#### Signal word

Danger

#### Hazard-determining components of labelling:

formaldehyde polymer with 1,3-benzenedimethanamine and phenol  
Benzyl alcohol  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
m-phenylenebis(methylamine)  
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine  
N-(3-(trimethoxysilyl)propyl)ethylenediamine  
phenole, styrenated

Hazard statements  
H332 Harmful if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P260	Do not breathe vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	

**· 2.3 Other hazards**· Results of PBT and vPvB assessment· PBT: Not applicable.· vPvB:

1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine

· Determination of endocrine-disrupting properties

61788-44-1 | phenole, styrenated

List II

**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 1950616-36-0 EC number: 701-207-5 Reg.nr.: 01-2119966906-20	formaldehyde polymer with 1,3-benzenedimethanamine and phenol Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	<10%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	<10%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-0000	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<10%

(Contd. on page 3)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: AkepoX 2040 Component B**

(Contd. of page 2)

CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	<10%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412 EUH071	1-5%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H332; Skin Sens. 1, H317 vPvB	1-5%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119979575-18	phenole, styrenated Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	1-5%
CAS: 108-95-2 EINECS: 203-632-7 Index number: 604-001-00-2 Reg.nr.: 01-2119471329-32	phenol Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Muta. 2, H341; STOT RE 2, H373 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Chronic 2, H411 Specific concentration limits: Skin Corr. 1B; H314: $C \geq 3 \%$ Skin Irrit. 2; H315: $1 \% \leq C < 3 \%$ Eye Irrit. 2; H319: $1 \% \leq C < 3 \%$	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- **General information:** Take affected persons out into the fresh air.  
Position and transport stably in side position.  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty  
Headache  
Dizziness  
Dizziness  
Coughing  
Nausea

(Contd. on page 4)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

#### Trade name: AkepoX 2040 Component B

(Contd. of page 3)

- Hazards Danger of impaired breathing.
- **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed, gastric irrigation with added, activated carbon.

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:  
Carbon monoxide (CO)  
Nitrogen oxides (NO<sub>x</sub>)  
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- Protective equipment: Wear fully protective suit.  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 4)

- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.  
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from oxidising agents.  
Store away from foodstuffs.
- Further information about storage conditions: Store receptacle in a well ventilated area.  
Keep container tightly sealed.
- Storage class: 8 A
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:

**108-95-2 phenol**

IOELV	Short-term value: 16 mg/m <sup>3</sup> , 4 ppm Long-term value: 8 mg/m <sup>3</sup> , 2 ppm Skin
-------	--

- DNELs

**1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol**

Oral	DNEL (Kurzzeit-akut)	3.33 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	3.33 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.00385-2.8 mg/kg bw/day (ARB) 0.000167-0.008 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	0.000385-0.28 mg/kg bw/day (ARB) 0.000167-0.008 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2-6 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	0.02-0.6 mg/m <sup>3</sup> Air (ARB)

**100-51-6 Benzyl alcohol**

Oral	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	40 mg/kg bw/day (ARB) 20 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	8 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	110 mg/m <sup>3</sup> Air (ARB) 27 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	22 mg/m <sup>3</sup> Air (ARB) 5.4 mg/m <sup>3</sup> Air (BEV)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	DNEL (Kurzzeit-akut)	0.3 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.3 mg/kg bw/day (BEV)

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: AkepoX 2040 Component B**

(Contd. of page 5)

Inhalative	DNEL (Kurzzeit-akut)	0.073 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	0.073 mg/m <sup>3</sup> Air (ARB)

**38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Dermal	DNEL ( Langzeit-wiederholt)	0.14 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	0.493 mg/m <sup>3</sup> Air (ARB)

**1477-55-0 m-phenylenebis(methylamine)**

Dermal	DNEL ( Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	0.2 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	1.2 mg/m <sup>3</sup> Air (ARB)

**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

Oral	DNEL (Langzeit-wiederholt)	2.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	5 mg/kg bw/day (ARB)
		17 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	5 mg/kg bw/day (ARB)
		2.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	35.3 mg/m <sup>3</sup> Air (ARB)
		8.7 mg/m <sup>3</sup> Air (BEV)

**61788-44-1 phenole, styrenated**

Oral	DNEL (Langzeit-wiederholt)	1.562 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	6.25 mg/kg bw/day (ARB)
		3.125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	11.02 mg/m <sup>3</sup> Air (ARB)
		2.717 mg/m <sup>3</sup> Air (BEV)

**108-95-2 phenol**

Oral	DNEL (Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	8 mg/m <sup>3</sup> Air (ARB)
		1.32 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol**

PNEC (wässrig)	30 mg/l (KA)
	0.002 mg/l (MW)
	0.02 mg/l (SW)
PNEC (fest)	0.0236 mg/kg Trockengew (BO)
	0.01 mg/kg Trockengew (MWS)
	0.1001 mg/kg Trockengew (SWS)

**100-51-6 Benzyl alcohol**

PNEC (wässrig)	39 mg/l (KA)
	0.1 mg/l (MW)
	1 mg/l (SW)
	2.3 mg/l (WAS)
PNEC (fest)	0.456 mg/kg Trockengew (BO)
	0.527 mg/kg Trockengew (MWS)
	5.27 mg/kg Trockengew (SWS)

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 6)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

PNEC (wässrig)	3.18 mg/l (KA)
	0.006 mg/l (MW)
	0.06 mg/l (SW)
	0.23 mg/l (WAS)
PNEC (fest)	1.121 mg/kg Trockengew (BO)
	0.578 mg/kg Trockengew (MWS)
	5.784 mg/kg Trockengew (SWS)

**38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

PNEC (wässrig)	10 mg/l (KA)
	0.00111 mg/l (MW)
	0.0111 mg/l (SW)
	0.111 mg/l (WAS)
PNEC (fest)	864 mg/kg Trockengew (BO)
	432 mg/kg Trockengew (MWS)
	4,320 mg/kg Trockengew (SWS)

**1477-55-0 m-phenylenebis(methylamine)**

PNEC (wässrig)	10 mg/l (KA)
	0.0094 mg/l (MW)
	0.094 mg/l (SW)
	0.152 mg/l (WAS)
PNEC (fest)	2.44 mg/kg Trockengew (BO)
	1.24 mg/kg Trockengew (MWS)
	12.4 mg/kg Trockengew (SWS)

**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

PNEC (wässrig)	25 mg/l (KA)
	0.0062 mg/l (MW)
	0.062 mg/l (SW)
	0.62 mg/l (WAS)
PNEC (fest)	0.0075 mg/kg Trockengew (BO)
	0.005 mg/kg Trockengew (MWS)
	0.05 mg/kg Trockengew (SWS)

**61788-44-1 phenole, styrenated**

PNEC (wässrig)	0.17 mg/l (KA)
	0 mg/l (MW)
	0.001 mg/l (SW)
PNEC (fest)	31.525 mg/kg Trockengew (BO)
	65.778 mg/kg Trockengew (MWS)
	65.778 mg/kg Trockengew (SWS)

**108-95-2 phenol**

PNEC (wässrig)	2.1 mg/l (KA)
	0.00077 mg/l (MW)
	0.0077 mg/l (SW)
PNEC (fest)	0.136 mg/kg Trockengew (BO)

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)


Revision: 31.10.2023

**Trade name: AkepoX 2040 Component B**

(Contd. of page 7)

0.00915 mg/kg Trockengew (MWS)

0.0915 mg/kg Trockengew (SWS)

- Additional information: The lists valid during the making were used as basis.
  - **8.2 Exposure controls**
  - Appropriate engineering controls No further data; see section 7.
  - Individual protection measures, such as personal protective equipment
  - General protective and hygienic measures:
    - Do not eat, drink, smoke or sniff while working.
    - Use skin protection cream for skin protection.
    - Clean skin thoroughly immediately after handling the product.
    - Keep away from foodstuffs, beverages and feed.
    - Immediately remove all soiled and contaminated clothing
    - Wash hands before breaks and at the end of work.
    - Do not inhale gases / fumes / aerosols.
    - Avoid contact with the eyes and skin.
  - Respiratory protection:
    - Short term filter device:
    - Filter A/P2
    - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - Hand protection
    - Preventive skin protection by use of skin-protecting agents is recommended.
    - After use of gloves apply skin-cleaning agents and skin cosmetics.
    - Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
    - STOKO EMULSION (<http://www.stoko.com>)
    - Skin protection recommendation for skin cleaning after product handling:
    - Kresto Classic (<http://debstoko.com>)
    - Skin protection agent recommendation for skin aftercare:
    - STOKO VITAN (<http://www.stoko.com>)
    - The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
    - This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
- 
- 

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
    - Butyl rubber, BR
    - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023


Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 8)

- Penetration time of glove material Value for the permeation: Level  $\leq$  6, 480 min  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
  - Butyl rubber, BR
  - Butoject (KCL, Art\_No. 897, 898)
  - Nitrile rubber, NBR
  - Camatril (KCL, Art\_No. 730, 731, 732, 733)
  - Dermatril (Art\_No. 740, 741, 742)
  - Chloroprene rubber, CR
  - Camapren (KCL, Art\_No. 720, 722, 726)
- As protection from splashes gloves made of the following materials are suitable:
  - Nitrile rubber, NBR
  - Camatril (KCL, 730, 731, 732, 733)
  - Chloroprene rubber, CR
  - Camapren (KCL, Art\_No. 720, 722, 726)
- Not suitable are gloves made of the following materials:
  - Natural rubber, NR
  - Fluorocarbon rubber (Viton)
  - Leather gloves
  - Strong material gloves
- Eye/face protection


Tightly sealed goggles
- Body protection: Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- General Information
- Colour: Yellowish
- Odour: Characteristic
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 100 °C
- Lower and upper explosion limit
- Lower: 1.2 Vol %
- Flash point: 101 °C (100-51-6 Benzyl alcohol)
- Auto-ignition temperature: 380 °C
- Decomposition temperature: > 250 °C
- pH Not determined.  
Not applicable
- Viscosity:
- Kinematic viscosity Not determined.  
Not applicable
- Dynamic: Not determined.  
Not applicable
- Solubility
- water: Not miscible or difficult to mix.
- Vapour pressure: Not determined.
- Density and/or relative density
- Density at 20 °C: 1.67 g/cm<sup>3</sup>

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: AkepoX 2040 Component B**

(Contd. of page 9)

**9.2 Other information**

- Appearance:
- Form: Pasty
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product does not present an explosion hazard.
- Solvent content:
- Organic solvents: 9.1 %
- Solids content: 37.1 %

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Void
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.  
Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Corrosive gases/vapours

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Oral	LD50	4,701 mg/kg
Dermal	LD50	21,437 mg/kg
Inhalative	LC50/4 h	>16.1 mg/l (rat)

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 10)

**1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,020 mg/kg (rat)

**100-51-6 Benzyl alcohol**

Oral	LD50	1,040 mg/kg (mouse)
		1,040 mg/kg (rabbit)
		1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
	NOAEL	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (rat)
		2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	>4.178 mg/l (rat) (OECD 403)
	LC50/48h	360 mg/l (daphnia magna)
		645 mg/l (goo)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	LD50	1,030 mg/kg (ATE)
		1,030 mg/kg (rat)
Dermal	NOAEL-Werte	>250 mg/kg (rat)
	LD50	1,840 mg/kg (rabbit)
Inhalative	LC50/4 h	>2,000 mg/kg (rat)
		>5.01 mg/l (rat)

**38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

**1477-55-0 m-phenylenebis(methylamine)**

Oral	LD50	930 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	1.34 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)

**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

Oral	LD50	2,995 mg/kg (rat)
	NOEL	≥500 mg/kg (rat) (OECD 422)
	NOAEL	≥500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	1.49 mg/l (rat)

**61788-44-1 phenole, styrenated**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>5,010 mg/kg (rabbit)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	158.3 mg/l (rat)

**108-95-2 phenol**

Oral	LD50	300 mg/kg (mouse)
------	------	-------------------

(Contd. on page 12)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 11)

Dermal	LD50	317 mg/kg (rat)
Inhalative	LC50/4 h	630 mg/kg (rat)
	LC50/8h	316 mg/l (rat)
		0.9 mg/l (rat)

- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

- Endocrine disrupting properties

61788-44-1 phenole, styrenated

List II

\* **SECTION 12: Ecological information**

· **12.1 Toxicity**

- Aquatic toxicity:

**1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol**

EC50	491.3 mg/l (BES)
EC50/48h	29.8 mg/l (daphnia magna)
EC50/72h	20.4 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	25.9 mg/l (Oncorhynchus mykiss)

**100-51-6 Benzyl alcohol**

EC50/24h	55-400 mg/l (daphnia magna)
EC50/96h	640 mg/l (Scenedesmus pluvialis)
EC50	2,100 mg/l (BES) (OECD 209)
	79 mg/l (Scenedesmus quadricauda)
EC10/16h	658 mg/l (pseudomonas putida)
EC50/48h	230 mg/l (daphnia magna) (OECD 202)
ErC50/72h	770 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC0	640 mg/l (Scenedesmus quadricauda)
EC50/16h	658 mg/l (pseudomonas putida)
EC50/30min	71.4 mg/l (Photobac. phosphoreum)
	400 mg/l (pseudomonas putida)
IC5/96h	640 mg/l (Scenedesmus quadricauda)
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)
NOEC/21d	51 mg/l (daphnia magna) (OECD211)
EC50/72h	770 mg/l (algae) (OECD 201)
	500 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	645 mg/l (goo)
	10 mg/l (lepomis macrochirus)
	8.9 mg/l (Oncorhynchus mykiss)
	460 mg/l (Pimephales promelas)

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 12)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC50/24h	44 mg/l (daphnia magna)
LC 0/96h	70 mg/l (piscis)
EC10/18h	1,120 mg/l (pseudomonas putida)
EC50/48h	23 mg/l (daphnia magna) (OECD TG 202)
ErC50/72h	>50 mg/l (Scenedesmus subspicatus) (EG 88/302)
NOEC/21d	3 mg/l (daphnia magna) (OECD 202)
EC10	11.2 mg/l (Desmodesmus subspicatus)
EC50/72h	37 mg/l (algae) (EG 88/302)
	>50 mg/l (Desmodesmus subspicatus)
	37 mg/l (Scenedesmus subspicatus)
LC50/96h	110 mg/l (Brachydanio rerio) (EG 84/449)
	110 mg/l (Leuciscus idus) (EG 84/449)

**38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC50	>1,000 mg/l (BES)
EL50/48h	11.1 mg/l (daphnia magna)
EL50/72h	79.4 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	70.7 mg/l (Oncorhynchus mykiss)
EC50/72h	11.3 mg/l (algae)

**1477-55-0 m-phenylenebis(methylamine)**

EC50/24h	35.1 mg/l (daphnia magna)
EC50/48h	15.2 mg/l (daphnia magna)
EC50/30min	>1,000 mg/l (BES)
NOEC/21d	4.7 mg/l (daphnia magna)
EC50/72h	12 mg/l (Scenedesmus subspicatus)
	32.1 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	87.6 mg/l (Oryzias latipes)
	>100 mg/l (Zebrabärbling)

**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

EC50	435 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)
IC50/72h	8.8 mg/l (algae) (OECD 201)
EC50/48h	81 mg/l (daphnia magna)
EC50/16h	67 mg/l (pseudomonas putida)
NOEC	3.1 mg/kg (algae) (OECD 201)
	≥1,000 mg/kg (Eisenia fetida ( Regenwürmer)) (OECD 207)
NOEC/21d	>1 mg/l (daphnia magna)
EC50/48h	87.4 mg/l (daphnia magna)
EC50/72h	5 mg/l (algae)
	126 mg/l (Scenedesmus subspicatus)
LC50/96h	344 mg/l (Brachydanio rerio)
	597 mg/l (Danio rerio.)
	168 mg/l (pimephales promelas)

(Contd. on page 14)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 13)

**61788-44-1 phenole, styrenated**

EC50	362 mg/l (BES) 3.8 mg/l (piscis)
EL50/48h	4.6 mg/l (daphnia magna)
EL50/72h	20.42 mg/l (CHV) 3.14 mg/l (Scenedesmus subspicatus)
LL50/96h	24 mg/l (Danio rerio.) 14.8 mg/l (piscis)
NOEC/21d	0.2 mg/l (daphnia magna)
EC50/72h	9.7 mg/l (algae)
LC50/96h	5.6 mg/l (Brachydanio rerio)

**108-95-2 phenol**

EC50/24h	21 mg/l (BO)
EC50/96h	61.1 mg/l (algae)
EC50/48h	3.1 mg/l (daphnia magna)
LC50/96h	8.9 mg/l (Oncorhynchus mykiss)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:**

1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine
-----------	--

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:** Do not allow product to reach ground water, water course or sewage system.  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- **Uncleaned packaging:**

- **Recommendation:** Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 15)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 14)

· Recommended cleansing agents: Alcohol

**SECTION 14: Transport information****· 14.1 UN number or ID number**· ADR, IMDG, IATA UN2735**· 14.2 UN proper shipping name**

· ADR 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, formaldehyde polymer with 1,3-benzenedimethanamine and phenol)

· IMDG, IATA POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, formaldehyde polymer with 1,3-benzenedimethanamine and phenol)

**· 14.3 Transport hazard class(es)**· ADR

· Class 8 (C7) Corrosive substances.  
 · Label 8

· IMDG, IATA

· Class 8 Corrosive substances.  
 · Label 8

**· 14.4 Packing group**· ADR, IMDG, IATA III**· 14.5 Environmental hazards:**· Marine pollutant: No**· 14.6 Special precautions for user**

· Hazard identification number (Kemler code): Warning: Corrosive substances.  
 80

· EMS Number: F-A,S-B

· Segregation groups (SGG18) Alkalis

· Stowage Category A

· Segregation Code SG35 Stow "separated from" SGG1-acids

**· 14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

(Contd. on page 16)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 15)

· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>Transport category</u>	3
· <u>Tunnel restriction code</u>	E
· <u>IMDG</u>	5L
· <u>Limited quantities (LQ)</u>	Code: E1
· <u>Excepted quantities (EQ)</u>	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, FORMALDEHYDE POLYMER WITH 1,3-BENZENEDIMETHANAMINE AND PHENOL), 8, III

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

- Information about limitation of use: Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 151.6 g/l

(Contd. on page 17)

EU



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 31.10.2023

Version number 4 (replaces version 3)

Revision: 31.10.2023

**Trade name: Akepox 2040 Component B**

(Contd. of page 16)

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

\* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· <u>Department issuing SDS:</u>	Laboratory
· <u>Date of previous version:</u>	29.06.2022
· <u>Version number of previous version:</u>	3
· <u>Abbreviations and acronyms:</u>	<p>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)</p> <p>ICAO: International Civil Aviation Organisation</p> <p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</p> <p>IMDG: International Maritime Code for Dangerous Goods</p> <p>IATA: International Air Transport Association</p> <p>GHS: Globally Harmonised System of Classification and Labelling of Chemicals</p> <p>EINECS: European Inventory of Existing Commercial Chemical Substances</p> <p>ELINCS: European List of Notified Chemical Substances</p> <p>CAS: Chemical Abstracts Service (division of the American Chemical Society)</p> <p>DNEL: Derived No-Effect Level (REACH)</p> <p>PNEC: Predicted No-Effect Concentration (REACH)</p> <p>LC50: Lethal concentration, 50 percent</p> <p>LD50: Lethal dose, 50 percent</p> <p>PBT: Persistent, Bioaccumulative and Toxic</p> <p>SVHC: Substances of Very High Concern</p> <p>vPvB: very Persistent and very Bioaccumulative</p> <p>Acute Tox. 3: Acute toxicity – Category 3</p> <p>Acute Tox. 4: Acute toxicity – Category 4</p> <p>Skin Corr. 1B: Skin corrosion/irritation – Category 1B</p> <p>Skin Irrit. 2: Skin corrosion/irritation – Category 2</p> <p>Eye Dam. 1: Serious eye damage/eye irritation – Category 1</p> <p>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</p> <p>Skin Sens. 1: Skin sensitisation – Category 1</p> <p>Skin Sens. 1A: Skin sensitisation – Category 1A</p> <p>Muta. 2: Germ cell mutagenicity – Category 2</p> <p>STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2</p> <p>Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2</p> <p>Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>