

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Akepox 5030 Component A

· Article number: 11381, 12203

DDH3-003T-H00T-KJVA · UFI:

 1.2 Relevant identified uses of the substance or mixture and

No further relevant information available. uses advised against

· Application of the substance / the

mixture Epoxy resin adhesive

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-642960 Fax. +49(0)911-644456 Lechstrasse 28 D 90451 Nürnberg e-mail info@akemi.de

· Further information obtainable

Laboratory

1.4 Emergency telephone

number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

H315 Causes skin irritation. Skin Irrit. 2

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

· Storage: Store in a well-ventilated place. Keep container tightly closed.

· 2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

· Signal word Warning

· Hazard-determining components of

labelling: bis[4-(2,3-epoxypropoxy)phenyl]propane

Cyclohexanedimethanol diglycidyl ether

· Hazard statements H315 Causes skin irritation.

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)



Page 2/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name:	Akepox 5030	Component A

		(Contd. of page 1)
 Precautionary statements 	P101	If medical advice is needed, have product container or label at
		· ·

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· Additional information: Contains epoxy constituents. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.√PvB: Not applicable.

· Determination of endocrine-

disrupting properties For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	25-50%
EINECS: 216-823-5	Aquatic Chronic 2, H411	
Index number: 603-073-00-2	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119456619-26-xxxx	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
CAS: 14228-73-0	Cyclohexanedimethanol diglycidyl ether	<12.5%
EINECS: 238-098-4 Reg.nr.: 01-2120068066-56-xxxx	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412 EUH205	
CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	1-5%
EINECS: 219-784-2 Reg.nr.: 01-2119513212-58	Eye Dam. 1, H318	
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

(Contd. of page 2)

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

Rinse out mouth and then drink plenty of water. After swallowing:

· 4.2 Most important symptoms and effects, both acute and

delayed

Breathing difficulty

Coughing Allergic reactions

· Hazards Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

CO2, powder or water spray. Fight larger fires with water spray or alcohol Suitable extinguishing agents:

resistant foam.

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

 Protective equipment: Wear fully protective suit.

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

 Additional information Collect contaminated fire fighting water separately. It must not enter the sewage

system.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

• 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Page 4/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle. Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from reducing agents.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Storage class:

No further relevant information available. · 7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

· DNELs		
1675-54-3	bis[4-(2,3-epoxypropoxy)pl	henyl]propane
Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB)
		0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m³ Air (ARB)
		0.87 mg/m³ Air (BEV)
14228-73-0 Cyclohexanedimethanol diglycidyl ether		
Oral	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (ARB)
		0.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	3.52 mg/m³ Air (ARB)
		0.86 mg/m³ Air (BEV)
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	21 mg/kg bw/day (ARB)
		(Contd. on page 5)



Page 5/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

<u>I rade</u>	<u>name:</u>	Akepox	5030	Component A
		_		-

|--|

		12.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	21 mg/kg bw/day (ARB)
		5 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	147 mg/m³ Air (ARB)
		43.5 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	147 mg/m³ Air (ARB)
		43.5 mg/m³ Air (BEV)

· PNECs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC (wässrig) 10 mg/l (KA) 0.0006 mg/l (MW) 0.006 mg/l (SW) 0.018 mg/l (WAS)

PNEC (fest)

0.065 mg/kg Trockengew (BO)

0.034 mg/kg Trockengew (MWS)

0.341 mg/kg Trockengew (SWS)

14228-73-0 Cyclohexanedimethanol diglycidyl ether

PNEC (wässrig) 0.6 mg/l (KA)

0.012 mg/l (MW) 0.117 mg/l (SW)

PNEC (fest) 0.24 mg/kg Trockengew (BO)

0.047 mg/kg Trockengew (MWS) 0.47 mg/kg Trockengew (SWS)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

PNEC (wässrig) 8.2 mg/l (KA)

0.1 mg/l (MW) 1 mg/l (SW) 1 mg/l (WAS)

PNEC (fest) 0.14 mg/kg Trockengew (BO)

0.36 mg/kg Trockengew (MWS) 3.6 mg/kg Trockengew (SWS)

Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· <u>Appropriate engineering controls</u> No further data; see section 7. · <u>Individual protection measures</u>, such as personal protective equipment

· General protective and hygienic

measures:

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin. Not necessary if room is well-ventilated.

• Respiratory protection: Not necessary if room is Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

(Contd. of page 5)

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898) Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Dermatril (KCL, Art No. 740, 741, 742)

Chloroprene rubber, CR

Camapren (KCL, Art No. 720, 722, 726)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

(Contd. on page 7)



(Contd. of page 6)

Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

· Eye/face protection

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic	phy	ysical and	chemical	pro	perties

General Information

· Colour: Dark beige · Odour: Characteristic

· Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range Undetermined.

· Flash point: Not applicable. · pH Not determined. Not applicable

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C: 109,000 mPas

Solubility

Not miscible or difficult to mix. · water:

· Vapour pressure at 20 °C: 2 hPa

Density and/or relative density

· Density at 20 °C: 1.56 g/cm³

• 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent separation test: Not applicable

· Solvent content:

44.2 % · Solids content:

· Information with regard to physical hazard classes

 Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void

· Gases under pressure Void · Flammable liquids Void

Void · Flammable solids · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

· Pyrophoric solids Void

· Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in

contact with water Void

· Oxidising liquids Void · Oxidising solids Void

· Organic peroxides Void · Corrosive to metals Void

(Contd. on page 8)



Page 8/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

(Contd. of page 7)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

No further relevant information available. · 10.1 Reactivity

· 10.2 Chemical stability · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous

May produce violent reactions with bases and numerous organic substances reactions

including alcohols and amines. Strong exothermic reaction with acids.

Reacts with reducing agents.

· 10.4 Conditions to avoid

No further relevant information available. No further relevant information available. · 10.5 Incompatible materials:

· 10.6 Hazardous decomposition

products: Irritant gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
1675-54-3	bis[4-(2,3-epo	xypropoxy)phenyl]propane	
Oral	LD50	>2,000 mg/kg (rat) (OECD 420)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)	
14228-73-	0 Cyclohexane	dimethanol diglycidyl ether	
Oral	LD50	1,098 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
2530-83-8	2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8,025 mg/kg (rat) (OECD 401)	
	NOAEL-Werte	≥5 mg/kg (mouse)	
		200 mg/kg (rabbit) (OECD 414)	
		500 mg/kg (rat) (OECD 415)	
Dermal	LD50	4,250 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50/4 h	>5.3 mg/l (rat) (OECD 403)	
	NOAEC	0.225 mg/l (rat) (OECD 412)	

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation. · Respiratory or skin sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)



(Contd. of page 8)

Page 9/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

A ti a tanci	-		
· Aquatic toxicity:			
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane			
	>100 mg/l (BES)		
	100 mg/l (pseudomonas putida)		
	1.8 mg/l (daphnia magna)		
	0.3 mg/l (daphnia magna)		
	11 mg/l (selenastrum capricornutum)		
	2 mg/l (Oncorhynchus mykiss)		
	Cyclohexanedimethanol diglycidyl ether		
EC50/48h	16.3 mg/l (daphnia magna)		
LC0/96h	10 mg/l (piscis)		
EC50/72h	36.6 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	13 mg/l (piscis)		
	10.1 mg/l (Oncorhynchus mykiss)		
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane			
EC50/96h	350 mg/l (Pseudokirchneriella subcapitata) (OECD 201)		
	>100 mg/l (salmon)		
EC50	119 mg/l (algae)		
IC50	255 mg/l (Scenedesmus subspicatus)		
EC50/48h	324 mg/l (daphnia magna)		
EC10/5h	1,500 mg/l (pseudomonas putida)		
ErC50/72h	350 mg/l (Selenastrum capricornutum)		
ECO/96h	44 mg/l (Cyprinus carpio)		
NOEC	>100 mg/kg (Klärschlamm: Atmungs-/Vermehrungshemmung) (OECD 209)		
NOEC/21d	≥100 mg/l (daphnia magna) (OECD 211)		
EC50/48h	324-710 mg/l (daphnia magna) (OECD 202)		
EC50/72h	255 mg/l (Scenedesmus subspicatus)		
LC50/96h	55 mg/l (Cyprinus carpio) (OECD 203)		
	276 mg/l (lem)		
	237 mg/l (Oncorhynchus mykiss)		
	1675-54-3 to 1C50 EC10/16h EC50/48h NOEC/21d EC50/72h LC50/96h 14228-73-0 EC50/48h LC0/96h EC50/72h LC50/96h EC50/96h EC50/96h EC50/96h EC50/48h EC10/5h EC10/5h EC0/96h NOEC NOEC/21d EC50/48h EC50/72h		

12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

12.5 Results of PBT and vPvB assessment

· <u>PBT:</u> Not applicable. · vPvB: Not applicable.

12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Remark: Toxic for fish

(Contd. on page 10)



(Contd. of page 9)

Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

· Additional ecological information:

· General notes:

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European	waste catalogue
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

SECTION 14: Transport information

· <u>14.1 UN number or ID number</u> · <u>ADR, IMDG, IATA</u>	UN3082
· 14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)
· <u>IMDG</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane), MARINE
	POLLUTANT
· <u>IATA</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)

· 14.3 Transport hazard class(es)

ADR



· Class 9 (M6) Miscellaneous dangerous substances and articles. · Label 9

· IMDG, IATA



· <u>Class</u> 9 Miscellaneous dangerous substances and articles. · <u>Label</u> 9

(Contd. on page 11)



Page 11/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

rade name: Akepox 5030 Component A	
	(Contd. of page 10
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):	Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
14.7 Maritime transport in bulk according to instruments	IMO Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
· Tunnel restriction code	(-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

PROPANE), 9, III

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the

application of lower-tier

requirements 200 t

Qualifying quantity (tonnes) for the

application of upper-tier

requirements 500 t

REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic

equipment – Annex II

None of the ingredients is listed.

(Contd. on page 12)





Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 5 (replaces version 4) Revision: 03.08.2023

Trade name: Akepox 5030 Component A

· REGULATION (EU) 2019/1148

(Contd. of page 11)

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· <u>Waterhazard class:</u> Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 0.0 g/l

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Department issuing SDS:Date of previous version:

.

Laboratory

21.12.2022

· Version number of previous

version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3