

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Akepox Panel Adhesive 7030 Komponente A**

Article number: 12593, 11593_A

UFI: XDE5-Q09H-X00T-036N

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

Signal word

Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing vapours.

(Contd. on page 2)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 1)

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.
 · vPvB: Not applicable.

· Determination of endocrine-disrupting properties

For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	bis[4-(2,3-epoxypropoxy)phenyl]propane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	12.5-25%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-0003	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	<10%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41-0005	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air. Position and transport stably in side position.

· After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: If skin irritation continues, consult a doctor. Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepox Panel Adhesive 7030 Komponente A

(Contd. of page 2)

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
Dizziness
Headache
Dizziness
Nausea
Allergic reactions
Danger of impaired breathing.

· Hazards

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear fully protective suit.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 3)

Store in cool, dry place in tightly closed receptacles.
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from reducing agents.
Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Protect from frost.
Keep container tightly sealed.

· Storage class:

12

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB)
		0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m ³ Air (ARB)
		0.87 mg/m ³ Air (BEV)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	DNEL (Langzeit-wiederholt)	6.25 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	104.15 mg/kg bw/day (ARB)
		62.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	29.39 mg/m ³ Air (ARB)
		8.7 mg/m ³ Air (BEV)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Oral	DNEL (Kurzzeit-akut)	0.83 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	1.7 mg/kg bw/day (BEV)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 4)

Inhalative	DNEL (Langzeit-wiederholt)	2.8 mg/kg bw/day (ARB) 1.7 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	4.9 mg/m ³ Air (ARB) 2.9 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	4.9 mg/m ³ Air (ARB)
		2.9 mg/m ³ Air (BEV)

· PNECs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC (wässrig)	10 mg/l (KA)
	0.0006 mg/l (MW)
	0.006 mg/l (SW)
	0.018 mg/l (WAS)
PNEC (fest)	0.065 mg/kg Trockengew (BO)
	0.034 mg/kg Trockengew (MWS)
	0.341 mg/kg Trockengew (SWS)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

PNEC (wässrig)	10 mg/l (KA)
	0.0003 mg/l (MW)
	0.003 mg/l (SW)
	0.025 mg/l (WAS)
PNEC (fest)	0.237 mg/kg Trockengew (BO)
	0.029 mg/kg Trockengew (MWS)
	0.294 mg/kg Trockengew (SWS)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

PNEC (wässrig)	1 mg/l (KA)
	0.00115 mg/l (MW)
	0.0115 mg/l (SW)
	0.115 mg/l (WAS)
PNEC (fest)	0.223 mg/kg Trockengew (BO)
	0.0283 mg/kg Trockengew (MWS)
	0.283 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 5)

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.
 Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
 STOKO EMULSION (<http://www.stoko.com>)
 Skin protection recommendation for skin cleaning after product handling:
 Kresto Classic (<http://debstoko.com>)
 Skin protection agent recommendation for skin aftercare:
 STOKO VITAN (<http://www.stoko.com>)
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR
 Chloroprene rubber, CR
 Nitrile rubber, NBR
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6 , 480 min
 The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butoject (KCL, Art_No. 897, 898)
 Nitrile rubber, NBR
 Camatril (KCL, Art_No. 730, 731, 732, 733)
 Dermatril (Art_No. 740, 741, 742)
 Chloroprene rubber, CR
 Camapren (KCL, Art_No. 720, 722, 726)
 Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Camatril (KCL, 730, 731, 732, 733)
 Chloroprene rubber, CR
 Butoject (KCL, Art_No. 897, 898)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 6)

- | | |
|--|---|
| <ul style="list-style-type: none"> · <u>Not suitable are gloves made of the following materials:</u> · <u>Eye/face protection</u> · <u>Body protection:</u> | <p>Camapren (KCL, Art_No. 720, 722, 726)
Butyl rubber, BR</p> <p>Leather gloves
Strong material gloves
Nitrile rubber, NBR</p> <div style="text-align: center;">  </div> <p>Tightly sealed goggles</p> <p>Protective work clothing</p> |
|--|---|

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- | | |
|---|-----------------------------------|
| · <u>General Information</u> | |
| · <u>Colour:</u> | Light grey |
| · <u>Odour:</u> | Specific type |
| · <u>Odour threshold:</u> | Not determined. |
| · <u>Melting point/freezing point:</u> | Undetermined. |
| · <u>Boiling point or initial boiling point and boiling range</u> | Undetermined. |
| · <u>Flammability</u> | Not applicable. |
| · <u>Lower and upper explosion limit</u> | |
| · <u>Lower:</u> | Not determined. |
| · <u>Upper:</u> | Not determined. |
| · <u>Flash point:</u> | Not applicable. |
| · <u>Auto-ignition temperature:</u> | >300 °C |
| · <u>Decomposition temperature:</u> | > 200 °C °C |
| · <u>pH</u> | Not determined.
Not applicable |
| · <u>Viscosity:</u> | |
| · <u>Kinematic viscosity</u> | Not determined. |
| · <u>Dynamic at 20 °C:</u> | 110,000 mPas |
| · <u>Solubility</u> | |
| · <u>water:</u> | Not miscible or difficult to mix. |
| · <u>Partition coefficient n-octanol/water (log value)</u> | Not determined. |
| · <u>Vapour pressure:</u> | Not determined. |
| · <u>Density and/or relative density</u> | |
| · <u>Density at 20 °C:</u> | 1.8 g/cm ³ |
| · <u>Relative density</u> | Not determined. |
| · <u>Vapour density</u> | Not determined. |

9.2 Other information

- | | |
|--|---|
| · <u>Appearance:</u> | |
| · <u>Form:</u> | Pasty |
| · <u>Important information on protection of health and environment, and on safety.</u> | |
| · <u>Ignition temperature:</u> | Product is not selfigniting. |
| · <u>Explosive properties:</u> | Product does not present an explosion hazard. |
| · <u>Solvent content:</u> | |
| · <u>Solids content:</u> | 63.4 % |
| · <u>Change in condition</u> | |
| · <u>Evaporation rate</u> | Not determined. |

Information with regard to physical hazard classes

- | | |
|--------------------------|------|
| · <u>Explosives</u> | Void |
| · <u>Flammable gases</u> | Void |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 7)

· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** May produce violent reactions with bases and numerous organic substances including alcohols and amines.
Reacts with strong acids.
Reacts with reducing agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

Oral	LD50	>2,000 mg/kg (rat) (OECD 420)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Oral	LD50	8,500 mg/kg (rat)
Dermal	LD50	>4,900 mg/kg (rabbit)
	LC50/48h	23.1 mg/l (algae)

- Primary irritant effect: Do not get in eyes, on skin, or on clothing.
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 8)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	1.8 mg/l (daphnia magna)
NOEC/21d	0.3 mg/l (daphnia magna)
EC50/72h	11 mg/l (selenastrum capricornutum)
LC50/96h	2 mg/l (Oncorhynchus mykiss)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

EC50/48h	2.55 mg/l (daphnia magna)
EC50/72h	1.8 mg/l (Selenastrum capricornutum)
LC50/96h	2.54 mg/l (Leuciscus idus)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

EC50/48h	23.1 mg/l (algae)
	67 mg/l (daphnia magna)
LC50/96h	30 mg/l (Leuciscus idus)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

- Remark: Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 10)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 9)

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:**· Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Alcohol**SECTION 14: Transport information****· 14.1 UN number or ID number****· ADR, IMDG, IATA**

UN3082

· 14.2 UN proper shipping name**· ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

· 14.3 Transport hazard class(es)**· ADR****· Class****· Label**

9 (M6) Miscellaneous dangerous substances and articles.

9

(Contd. on page 11)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 10)

· IMDG, IATA

· Class 9 Miscellaneous dangerous substances and articles.
 · Label 9

· **14.4 Packing group**

· ADR, IMDG, IATA III

· **14.5 Environmental hazards:**

· Marine pollutant: Yes
 Symbol (fish and tree)
 · Special marking (ADR): Symbol (fish and tree)
 · Special marking (IATA): Symbol (fish and tree)

· **14.6 Special precautions for user**

· Hazard identification number (Kemler code): Warning: Miscellaneous dangerous substances and articles.
 90
 · EMS Number: F-A,S-F
 · Stowage Category A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information: Not dangerous according to the above specifications.

· ADR

· Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 · Transport category 3
 · Tunnel restriction code (-)

· IMDG

· Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE AND 2-({2-[4-(OXIRAN-2-YLMETHOXY)BENZYL]PHENOXY}METHYL)OXIRANE AND 2,2'-[METHYLENEBIS(2,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE), 9, III

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

(Contd. on page 12)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepo Panel Adhesive 7030 Komponente A

(Contd. of page 11)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 0.0 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory

· Date of previous version: 28.02.2022

· Version number of previous version: 3

· Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.11.2023

Version number 4 (replaces version 3)

Revision: 08.11.2023

Trade name: Akepox Panel Adhesive 7030 Komponente A

(Contd. of page 12)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU