

Tel. +49(0)911-642960

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

<u>Trade name:</u>
 <u>Article number:</u>
 UFI:
 <u>Easy Filler Green +</u>
 87113, 87114, 87118
 X877-60MY-A00Y-NAJN

1.2 Relevant identified uses of the substance or mixture and

uses advised against

No further relevant information available.

Application of the substance / the

Mixture Knife filler/ Surfacer Polyester resin

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Lechstrasse 28 Fax. +49(0)911-644456 D 90451 Nürnberg e-mail info@akemi.de

· Further information obtainable

from: Laboratory

· 1.4 Emergency telephone

<u>number:</u> Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

· Storage: Store in a well-ventilated place. Keep cool.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.





GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of

labelling: unsaturated Polyester resin

stvrene

· Hazard statements H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +		
		(Contd. of page 1)
	H332 Harmful if	inhaled.
	H315 Causes s	kin irritation.
	H319 Causes s	erious eye irritation.
		d of damaging the unborn child.
	H372 Causes of	lamage to the hearing organs through prolonged or repeated
	exposure.	
		o aquatic life with long lasting effects.
· Precautionary statements	P101	If medical advice is needed, have product container or label at
		hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and
		other ignition sources. No smoking.
	P260	Do not breathe vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves / eye protection.
	P302+P352	IF ON SKIN: Wash with plenty of water.
	P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do. Continue
		rinsing.
	P314	Get medical advice/attention if you feel unwell.
	P403+P235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local/
		regional/national/international regulations.
· 2.3 Other hazards		
 Results of PBT and vPvB assessr 		
· <u>PBT:</u>	Not applicable.	
· vPvB:	Not applicable.	
 Determination of endocrine- 		
disrupting properties	For information o	n endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	unsaturated Polyester resin	12.5-25%
	Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-25%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40-0000	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· <u>General information:</u> Take affected persons out into the fresh air.

(Contd. on page 3)



(Contd. of page 2)

Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

 After inhalation: Supply fresh air; consult doctor in case of complaints.

If skin irritation continues, consult a doctor. · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness Dizziness Nausea

· Hazards Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

Water with full jet

· For safety reasons unsuitable

extinguishing agents:

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage

system.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 4)



Page 4/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

<u>Trade name:</u> Easy Filler Green +

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

<u>handling</u> Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than

air).

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

· Requirements to be met by

<u>storerooms and receptacles:</u> Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class: 3

· <u>7.3 Specific end use(s)</u> No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

· <u>DNELs</u>		
100-42-5 styrene		
Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	406 mg/kg bw/day (ARB)
		343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m³ Air (ARB)
		174.25-182.75 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	85 mg/m³ Air (ARB)
		10.2 mg/m³ Air (BEV)
7779-90-0	trizinc bis(orthophosphate	
Oral	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	83 mg/kg bw/day (ARB)
		83 mg/kg bw/day (BEV)

(Contd. on page 5)



Page 5/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

<u>Trade name:</u> Easy Filler Green +

(Contd. of page 4)

Inhalative	DNEL (Langzeit-wiederholt)	5 mg/m³ Air (ARB)
		2.5 mg/m³ Air (BEV)

· PNECs

100-42-5 styrene

PNEC (wässrig) 5 mg/l (KA)

0.014 mg/l (MW) 0.028 mg/l (SW) 0.04 mg/l (WAS)

PNEC (fest)

0.2 mg/kg Trockengew (BO)

0.307 mg/kg Trockengew (MWS) 0.614 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures:

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

· Hand protection

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of

protective gloves:

ARRETIL (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Skin protection agent recommendation for skin aftercare:

Kresto Classic (http://debstoko.com) STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL

GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH,

Germany, 36124 Eichenzell, internet: http://www.kcl.de).

(Contd. on page 6)



Page 6/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +

(Contd. of page 5)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

· Not suitable are gloves made of the following materials:

Chloroprene rubber, CR

Leather gloves

Strong material gloves

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Colour: Light green
 Odour: Specific type
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range

145.2 °C (100-42-5 styrene)

· Lower and upper explosion limit

• <u>Lower:</u> 1.2 Vol % • Upper: 8.9 Vol %

• Flash point: 31 °C (100-42-5 styrene)

· Auto-ignition temperature: 480 °C

Not determined.
Not applicable

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +

(Contd. of page 6)

· Viscosity:

· Kinematic viscosity

Not applicable.

Not determined.

· Dynamic: Not applicable.

Not determined.

Solubility

· water: · Vapour pressure at 20 °C: Not miscible or difficult to mix.

6 hPa

Density and/or relative density

· Density at 20 °C:

1.48 g/cm³

• 9.2 Other information

· Appearance:

· Form:

Structurally viscous

· Important information on protection of health and

environment, and on safety.

· Ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Solvent content:

· Organic solvents:

18.8 % 46.1 %

· Solids content:

· Information with regard to physical hazard classes Explosives

Void

· Flammable gases

Void

· Aerosols Oxidising gases Void

· Gases under pressure

Void Void

· Flammable liquids

Flammable liquid and vapour.

· Flammable solids

Void

· Self-reactive substances and mixtures

Void

· Pyrophoric liquids · Pyrophoric solids

Void

Void Void

Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases in contact with water

Void

Oxidising liquids

Void

Oxidising solids

Void

· Organic peroxides

Void

· Corrosive to metals Desensitised explosives Void Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous

reactions

Exothermic polymerisation.

Reacts with peroxides and other radical forming substances.

Reacts with strong alkali. Reacts with strong acids.

Reacts with strong oxidising agents.

· 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 8)



(Contd. of page 7)

Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

<u>Trade name:</u> Easy Filler Green +

No further relevant information available.

· 10.6 Hazardous decomposition

10.5 Incompatible materials:

products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

LD/LC50 values relevant for classification	<u>n:</u>
ATF (Acute Toxicity Estimates)	

· · · · · · · · · · · · · · · · · · ·		,,
		2,162 mg/kg (rat)
Inhalative	LC50/4 h	5.88 mg/l (rat)

unsatui	rated Polye	ester resin
<u> </u>	. 5 5 6	=00 (1

		500 mg/kg (ATE)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

100-42-5 styrene

Oral		>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m3 (mouse)
		11,800 mg/m3 (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)

7779-90-0 trizinc bis(orthophosphate)

		>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.7 mg/l (rat)

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation
Germ cell mutagenicity
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

· Reproductive toxicity Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· <u>A</u> c	luatic	toxicity:	
--------------	--------	-----------	--

100-42-5 styrene

EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)

5.5 mg/l (Photobac. phosphoreum)

IC50/72h 4.9 mg/l (algae)

1.4 mg/l (selenastrum capricornutum)

(Contd. on page 9)



Page 9/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +

			(Contd. of page 8)			
	IC5/8d	>200 mg/l (Scenedesmus quadricauda)				
	EC10/16h 72 mg/l (pseudomonas putida)					
	EC50/16h >72 mg/l (pseudomonas putida)					
	EC50/8d >200 mg/l (Scenedesmus quadricauda)					
EC50/72u >1-<10 mg/l (algae)						
EC20/0.5h 140 mg/l (BES) (OECD 209)						
	NOEC/21d 1.01 mg/l (daphnia magna)					
	EC10 0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)					
EC50/48h 0.56 mg/l (algae)						
3.3-7.4 mg/l (daphnia magna)						
EC50/72h 0.46-4.3 mg/l (Pseudokirchneriella subcapitata)						
LC50/96h >1-<10 mg/l (piscis)						
19.03-33.53 mg/l (lem)						
3.24-4.99 mg/l (pimephales promelas)						
6.75-14.5 mg/l (Pimephales promelas)						
		58.75-95.32 mg/l (poecilia reticulata)				
	LC50/72h 4.9 mg/l (algae)					
7779-90-0 trizinc bis(orthophosphate)						
	EC50/48h	28.2 mg/l (daphnia magna)				
	ErC50/72h	<0.3 mg/l (Desmodesmus subspicatus)				
	EC50/48h	<1.7 mg/l (daphnia magna)				
	EC50/72h	0.28 mg/l (Selenastrum capricornutum)				

· 12.2 Persistence and

degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available. 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment Not applicable. · PBT: · vPvB: Not applicable.

LC50/96h <5.1 mg/l (Oncorhynchus mykiss)

12.6 Endocrine disrupting

properties 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

The product does not contain substances with endocrine disrupting properties.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue						
	20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS					
	20 01 00	separately collected fractions (except 15 01)					
1 7		(Contd. on page 10)					



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

<u>Trade name:</u> Easy Filler Green +

(Contd. of page 9)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

٠,	14.1	UN	number	or ID	number
----	------	----	--------	-------	--------

· ADR, IMDG, IATA UN3269

· 14.2 UN proper shipping name

• ADR 3269 POLYESTER RESIN KIT POLYESTER RESIN KIT

14.3 Transport hazard class(es)

· ADR



· <u>Class</u> 3 (F3) Flammable liquids.

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

14.4 Packing group

· <u>ADR, IMDG, IATA</u> III

· 14.5 Environmental hazards:

· Marine pollutant:

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

· EMS Number: F-E,S-D
· Stowage Category A

· 14.7 Maritime transport in bulk according to IMO

<u>instruments</u> Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport category 3

Tunnel restriction code E

· Remarks: Without hardener component: no dangerous goods < 450 l

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

<u>Trade name:</u> Easy Filler Green +

(Contd. of page 10)

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: See SP340

Remarks: Without hardener component: no dangerous goods < 30 l

·IATA

· Remarks: Without hardener component: 3/III UN 1866 Resin Solution

· UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.
Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the

application of lower-tier

requirements 5,000 t

Qualifying quantity (tonnes) for the

application of upper-tier

requirements 50,000 t

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 279.0 g/l

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 5 (replaces version 4) Revision: 24.10.2023

Trade name: Easy Filler Green +

(Contd. of page 11)

 DECOPAINT: subject to EUregulations 2004/42/EG (ANNEX

EU Grenzwert für dieses Produkt (Produktkategorie (Kat. B/b)): 250 g/l (2007) /

250 g/l (2010).

Das Produkt enthält max. 150 g/l VOC.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

 Department issuing SDS: · Date of previous version:

31.01.2022

Laboratory

· Version number of previous version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3