

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Darkener Super**
- Article number: 10939, 10940, 10941, 10942, 10943, 10944
- UFI: M1J8-KHEQ-701T-NVC4

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Application of the substance / the mixture Protective impregnation

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-642960
Lechstrasse 28 Fax. +49(0)911-644456
D 90451 Nürnberg e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

2,2,4,6,6-pentamethylheptan
Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics
H226 Flammable liquid and vapour.

Hazard statements

H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 1)

P302+P352 IF ON SKIN: Wash with plenty of water.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 EUH066 Repeated exposure may cause skin dryness or cracking.

· Additional information:· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.· vPvB: Not applicable.**SECTION 3: Composition/information on ingredients**· **3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

13475-82-6	2,2,4,6,6-pentamethylheptan Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EUH066	25-50%
	Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	25-50%
67-56-1	methanol Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	<1%
123-86-4	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**· General information:

Take affected persons out into the fresh air.
 Position and transport stably in side position.
 Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

If skin irritation continues, consult a doctor.

· After eye contact:

Immediately wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
 Headache
 Dizziness
 Dizziness

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 2)

- Hazards Nausea
Profuse sweating
Danger of impaired breathing.
- **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
Wear self-contained respiratory protective device.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 3)

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Use only in well ventilated areas.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class:

3

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

67-56-1 methanol

IOELV	Long-term value: 260 mg/m ³ , 200 ppm
	Skin

123-86-4 n-butyl acetate

IOELV	Short-term value: 723 mg/m ³ , 150 ppm
	Long-term value: 241 mg/m ³ , 50 ppm

· DNELs

67-56-1 methanol

Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	130 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	26 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	130 mg/m ³ Air (ARB)
		26 mg/m ³ Air (BEV)

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	6 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	7 mg/kg bw/day (ARB)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 4)

Inhalative	DNEL (Kurzzeit-akut)	3.4 mg/kg bw/day (BEV) 600 mg/m ³ Air (ARB) 300 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	48-300 mg/m ³ Air (ARB) 12-35.7 mg/m ³ Air (BEV)

· PNECs

67-56-1 methanol

PNEC (wässrig)	100 mg/l (KA)
	2.08 mg/l (MW)
	20.8 mg/l (SW)
	1,540 mg/l (WAS)
PNEC (fest)	100 mg/kg Trockengew (BO)
	7.7 mg/kg Trockengew (MWS)
	77 mg/kg Trockengew (SWS)

123-86-4 n-butyl acetate

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Apply solvent resistant skin cream before starting work.
Use skin protection cream for skin protection.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Filter AX

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

STOKODERM (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 5)

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye/face protection

Tightly sealed goggles

· Body protection:

Protective work clothing

* **SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Colour:

Colourless

· Odour:

Characteristic

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 6)

· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	180 °C
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	0.6 Vol %
· <u>Upper:</u>	7 Vol %
· <u>Flash point:</u>	44 °C
· <u>Ignition temperature:</u>	240 °C
· <u>pH</u>	Not determined. Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity at 20 °C</u>	11 s (DIN 53211/4)
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	1 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.85 g/cm ³

9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Fluid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	59.9 %
· <u>Solids content:</u>	29.8 %

· Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Flammable liquid and vapour.
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
	Void

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 7)

- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
Forms flammable gases/fumes.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	50,000 mg/kg (rat)
Dermal	LD50	150,000 mg/kg

13475-82-6 2,2,4,6,6-pentamethylheptan

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	2,200-2,500 mg/kg (rabbit) (OECD 402)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 8)

Inhalative	LC50/8h	>5 ppm (rat)
	LC50/48h	>3,193 mg/l (daphnia magna) (ISO 14559)

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5 mg/l (rat)
	LC50/48h	>1,000 mg/l (daphnia magna) (OECD 202)

67-56-1 methanol

Oral	LD50	100 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
		300 mg/kg (rat)
Inhalative	LC50/4 h	128.2 mg/l (rat)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	>14,112 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m ³ (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

· 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity**

- Aquatic toxicity:

13475-82-6 2,2,4,6,6-pentamethylheptan

IC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	>1,000 mg/l (daphnia magna)
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata) (OECD201)
NOELR/21d	0.02 mg/l (daphnia magna) (OECD 211)
NOELR/28d	0.267 mg/l (Oncorhynchus mykiss) ((Q)SAR)
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

EL0/48h	1,000 mg/l (daphnia magna)
EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 9)

NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOELR/21d	<1 mg/l (daphnia magna) (OECD 211)
NOELR/28d	0.192 mg/l (Oncorhynchus mykiss) ((Q)SAR)
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)

67-56-1 methanol

EC50/96h	22,000 mg/l (Pseudokirchneriella subcapitata)
IC50	>1,000 mg/l (BES)
EC50/48h	>10,000 mg/l (daphnia magna)
LC50/96h	13,500-17,600 mg/l (Iem) 19,500-20,700 mg/l (Oncorhynchus mykiss) 28,200 mg/l (pimephales promelas)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest) 674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.) 81 mg/l (piscis) 100 mg/l (Iepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (pimephales promelas) (OECD 203)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:**

Not applicable.

- **vPvB:**

Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 10)

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods**

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 13*	solvents

· Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information**· 14.1 UN number or ID number**

· ADR, IMDG, IATA UN3295

· 14.2 UN proper shipping name

· ADR 3295 HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan), ENVIRONMENTALLY HAZARDOUS

· IMDG HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan), MARINE POLLUTANT

· IATA HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan)

· 14.3 Transport hazard class(es)· ADR

· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG

· Class 3 Flammable liquids.

· Label 3

· IATA

· Class 3 Flammable liquids.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 11)

· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-D A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.S. (HYDROCARBONS, C10-C12, ISOALKANES, <2% AROMATICS, 2,2,4,6,6-PENTAMETHYLHEPTAN), 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 69

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 13)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3 (replaces version 2)

Revision: 19.07.2022

Trade name: Darkener Super

(Contd. of page 12)

· REGULATION (EU) 2019/1148· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 506.2 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory· Date of previous version: 03.06.2022· Version number of previous version: 2

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4