

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Autobody Filler No.4 styrene free**

Article number: 20910, 20911, 20912, 20913

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Knife filler/ Surfacer
Polyester resin

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07

· Signal word

Warning

· Hazard-determining components of labelling:

Not applicable.

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

During processing and product hardening the network generator is released as fume. Consequently, take care for adequate air conditioning and for fume exhaustion on request.

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· Results of PBT and vPvB assessment· PBT: Not applicable.· vPvB: Not applicable.* **SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 25013-15-4 EINECS: 246-562-2 Reg.nr.: 01-2119622074-50-0000	vinyltoluene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<12.5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40-0000	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
EC number: 911-490-9 Reg.nr.: 01-2119979579-10	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<1%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Breathing difficulty
Profuse sweating
Nausea
Dizziness
Dizziness

· Hazards

Danger of impaired breathing.
Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

· 5.3 Advice for firefighters

- Protective equipment: Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Dispose of the material collected according to regulations.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
Store away from oxidising agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:**
No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 4)

· DNELs**25013-15-4 vinyltoluene**Inhalative DNEL (Langzeit-wiederholt) 37 mg/m³ Air (ARB)**7779-90-0 trizinc bis(orthophosphate)**

Oral DNEL (Langzeit-wiederholt) 0.83 mg/kg bw/day (BEV)

Dermal DNEL (Langzeit-wiederholt) 83 mg/kg bw/day (ARB)

83 mg/kg bw/day (BEV)

Inhalative DNEL (Langzeit-wiederholt) 5 mg/m³ Air (ARB)2.5 mg/m³ Air (BEV)**Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol**

Oral DNEL (Langzeit-wiederholt) 0.83 mg/kg bw/day (BEV)

Dermal DNEL (Langzeit-wiederholt) 1.4 mg/kg bw/day (ARB)

0.83 mg/kg bw/day (BEV)

Inhalative DNEL (Langzeit-wiederholt) 9.8 mg/m³ Air (ARB)2.9 mg/m³ Air (BEV)· PNECs**25013-15-4 vinyltoluene**

PNEC (wässrig) 1 mg/l (KA)

0.002 mg/l (MW)

0.0498 mg/l (SW)

PNEC (fest) 0.133 mg/kg Trockengew (BO)

0.0684 mg/kg Trockengew (MWS)

0.684 mg/kg Trockengew (SWS)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

PNEC (wässrig) 10 mg/l (KA)

0.005 mg/l (MW)

0.048 mg/l (SW)

PNEC (fest) 0.21 mg/kg Trockengew (BO)

0.12 mg/kg Trockengew (MWS)

1.2 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 5)

the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

ARRETIL (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (<http://debstoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

- Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

- As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

- Not suitable are gloves made of the following materials:

Chloroprene rubber, CR

Leather gloves

Strong material gloves

- Eye protection:

**Tightly sealed goggles**

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

· Body protection: Protective work clothing

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form: Structurally viscous

Colour: Beige

· Odour: Characteristic

· pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 145 °C

· Flash point: 32 °C

· Ignition temperature: 480 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.1 Vol %

Upper: 5.3 Vol %

· Vapour pressure at 20 °C: 6 hPa

· Density at 20 °C: 1.93 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic at 20 °C: 80,000 mPas

Kinematic: Not determined.

· Solvent content:

Organic solvents: 11.6 %

Solids content: 87.7 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

Exothermic polymerisation.
Reacts with peroxides and other radical forming substances.
Reacts with strong alkali.
Reacts with strong acids.
Reacts with strong oxidising agents.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 7)

Organic phosphorus compounds
Possible in traces.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	>77.6 mg/l
------------	----------	------------

25013-15-4 vinyltoluene

Oral	LD50	3,680 mg/kg (rat)
	NOAEL	600 mg/kg (rat)
Dermal	LD50	4,490 mg/kg (rabbit)
Inhalative	LC50/4h	>3,535 mg/m ³ (rat)
	LC50/4 h	11 mg/l (ATE)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.7 mg/l (rat)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

Oral	LD50	619 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

· Aquatic toxicity:

25013-15-4 vinyltoluene

EC50	2.6 mg/l (Bluegill.)
EC50/48h	1.3 mg/l (daphnia magna)
NOELR/72h	1.6 mg/l (green alge)
NOEC/21d	0.498 mg/l (daphnia magna)
	0.563 mg/l (piscis)
EC50/72h	5.2 mg/l (Fathead minnow)
	2.6 mg/l (selenastrum capricornutum)
LC50/96h	5.2-23.4 mg/l (piscis)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 8)

7779-90-0 trizinc bis(orthophosphate)

EC50/48h	28.2 mg/l (daphnia magna)
ErC50/72h	<0.3 mg/l (Desmodesmus subspicatus)
EC50/48h	<1.7 mg/l (daphnia magna)
EC50/72h	0.28 mg/l (Selenastrum capricornutum)
LC50/96h	<5.1 mg/l (Oncorhynchus mykiss)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

EC50/48h	48 mg/l (daphnia magna)
EC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Cyprinus carpio)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- Ecotoxicological effects:

- Remark:

Harmful to fish

- Additional ecological information:

- General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- **12.5 Results of PBT and vPvB assessment**

- PBT:

Not applicable.

- vPvB:

Not applicable.

- **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- Uncleaned packaging:

- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

- Recommended cleansing agents:

Alcohol
acetone**SECTION 14: Transport information**

- **14.1 UN-Number**

- ADR, IMDG, IATA

UN3269

- **14.2 UN proper shipping name**

- ADR

3269 POLYESTER RESIN KIT

- IMDG, IATA

POLYESTER RESIN KIT

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F3) Flammable liquids.
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Flammable liquids.
· Danger code (Kemler): -
· EMS Number: F-E,S-D
· Stowage Category A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
· Transport category 3
· Tunnel restriction code E
· Remarks: Without hardener component: no dangerous goods < 450 l

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: See SP340
· Remarks: Without hardener component: no dangerous goods < 30 l

· IATA

· Remarks: Without hardener component: 3/III UN 1866 Resin Solution

· UN "Model Regulation":

UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EWG (2008/47/EG); 453/2010/EG

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 4

Revision: 06.05.2019

Trade name: Autobody Filler No.4 styrene free

(Contd. of page 11)

Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB