

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

- Trade name: **Interior Paint**
- Article number: 87420, 87421, 87422, 87423
- UFI: 2AH0-A0WG-H00C-HH6D

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Application of the substance / the mixture: Priming  
Lacquer
- No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg
- Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

- Further information obtainable from: Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of water.
- Storage: Store in a well-ventilated place. Keep cool.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Store locked up.

#### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

- Signal word: Danger

- Hazard-determining components of labelling:

- Hazard statements: acetone  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 1)

· <u>Precautionary statements</u>	P101 P102 P103 P210  P211 P251 P260 P280 P305+P351+P338  P410+P412  P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Wear eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international regulations.
· <u>Additional information:</u>	EUH066 Repeated exposure may cause skin dryness or cracking. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Buildup of explosive mixtures possible without sufficient ventilation.	
· <b>2.3 Other hazards</b>		
· Results of PBT and vPvB assessment		
· <u>PBT:</u>	Not applicable.	
· <u>vPvB:</u>	Not applicable.	

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**· Description: Mixture: consisting of the following components.· Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	12.5-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<12.5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8 Reg.nr.: 01-2119485395-27	isobutane (containing $\geq 0,1\%$ butadiene (203-450-8)) Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	1-5%

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 2)

CAS: 9004-70-0 Index number: 603-037-00-6	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	1-5%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide Carc. 2, H351	1-5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin. Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty  
Dizziness  
Headache  
Dizziness  
Nausea

**4.3 Hazards**

Danger of impaired breathing.

**4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.  
If swallowed or in case of vomiting, danger of entering the lungs.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.

**For safety reasons unsuitable extinguishing agents:**

Water with full jet

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:  
Carbon monoxide (CO)  
Formation of toxic gases is possible during heating or in case of fire.  
Can form explosive gas-air mixtures.

**5.3 Advice for firefighters**

- Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name:** Interior Paint

(Contd. of page 3)

Do not inhale explosion gases or combustion gases.

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation  
Keep away from ignition sources.

· **6.2 Environmental precautions:**

Wear protective equipment. Keep unprotected persons away.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Use only in well ventilated areas.  
Take note of emission threshold.

· **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:**

Not required.

· **Further information about storage conditions:**

Protect from frost.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

· **Storage class:**

2 B

· **7.3 Specific end use(s)**

No further relevant information available.

(Contd. on page 5)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name:** Interior Paint

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

**67-64-1 acetone**IOELV Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm**123-86-4 n-butyl acetate**IOELV Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm**108-65-6 2-methoxy-1-methylethyl acetate**IOELV Short-term value: 550 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 275 mg/m<sup>3</sup>, 50 ppm  
Skin**reaction mass of ethylbenzole and xylene**AGW Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
H

· DNELs

**67-64-1 acetone**

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	186 mg/kg bw/day (ARB)
		62 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	1,210 mg/m <sup>3</sup> Air (ARB)
		200 mg/m <sup>3</sup> Air (BEV)

**123-86-4 n-butyl acetate**

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
		6 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	7 mg/kg bw/day (ARB)
Inhalative		3.4 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	960 mg/m <sup>3</sup> Air (ARB)
		859.7 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	480 mg/m <sup>3</sup> Air (ARB)
		102.34 mg/m <sup>3</sup> Air (BEV)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	DNEL (Langzeit-wiederholt)	1.67 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	153.5 mg/kg bw/day (ARB)
		54.8 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	550 mg/m <sup>3</sup> Air (ARB)
		33 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	275 mg/m <sup>3</sup> Air (ARB)
		33 mg/m <sup>3</sup> Air (BEV)

**reaction mass of ethylbenzole and xylene**

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
------	----------------------------	------------------------

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 5)

Dermal	DNEL ( Langzeit-wiederholt)	180 mg/kg bw/day (ARB) 108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-442 mg/m <sup>3</sup> Air (ARB) 174 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	77-221 mg/m <sup>3</sup> Air (ARB) 14.8-65.3 mg/m <sup>3</sup> Air (BEV)

**13463-67-7 titanium dioxide**

Oral	DNEL (Langzeit-wiederholt)	700 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	10 mg/m <sup>3</sup> Air (ARB)

**64-17-5 ethanol**

Oral	DNEL (Langzeit-wiederholt)	87 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	950 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	343 mg/kg bw/day (ARB) 206 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,900 mg/m <sup>3</sup> Air (ARB) 950 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	950 mg/m <sup>3</sup> Air (ARB) 114 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**67-64-1 acetone**

PNEC (wässrig)	100 mg/l (KA) 1.06 mg/l (MW) 10.6 mg/l (SW) 21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO) 3.04 mg/kg Trockengew (MWS) 30.4 mg/kg Trockengew (SWS)

**123-86-4 n-butyl acetate**

PNEC (wässrig)	35.6 mg/l (KA) 0.018 mg/l (MW) 0.18 mg/l (SW) 0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO) 0.0981 mg/kg Trockengew (MWS) 0.981 mg/kg Trockengew (SWS)

**108-65-6 2-methoxy-1-methylethyl acetate**

PNEC (wässrig)	100 mg/l (KA) 0.0635 mg/l (MW) 0.635 mg/l (SW) 6.35 mg/l (WAS)
PNEC (fest)	0.29 mg/kg Trockengew (BO) 0.329 mg/kg Trockengew (MWS) 3.29 mg/kg Trockengew (SWS)

**reaction mass of ethylbenzole and xylol**

PNEC (wässrig)	6.58 mg/l (KA)
----------------	----------------

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 6)

PNEC (fest)	0.327 mg/l (MW) 0.327 mg/l (SW) 2.31 mg/kg Trockengew (BO) 12.46 mg/kg Trockengew (MWS) 12.46 mg/kg Trockengew (SWS)
<b>13463-67-7 titanium dioxide</b>	
PNEC (wässrig)	100 mg/l (KA) 1 mg/l (MW) 0.127 mg/l (SW)
PNEC (fest)	100 mg/kg Trockengew (BO) 100 mg/kg Trockengew (MWS) 1,000 mg/kg Trockengew (SWS)
<b>64-17-5 ethanol</b>	
PNEC (wässrig)	580 mg/l (KA) 0.79 mg/l (MW) 0.96 mg/l (SW) 2.75 mg/l (WAS)
PNEC (fest)	0.63 mg/kg Trockengew (BO) 0.72 mg/kg Trockengew (FUT) 2.9 mg/kg Trockengew (MWS) 3.6 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.  
Use skin protection cream for skin protection.  
Clean skin thoroughly immediately after handling the product.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

- Respiratory protection:

Filter AX  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Preventive skin protection by use of skin-protecting agents is recommended.  
After use of gloves apply skin-cleaning agents and skin cosmetics.  
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

- Hand protection

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 7)

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level  $\leq$  6, 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Butoject (KCL, Art\_No. 897, 898)

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Neoprene gloves

Leather gloves

Strong material gloves

· Eye/face protection**Tightly sealed goggles**· Body protection:

Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**· General Information· Colour:

According to product specification

· Odour:

Specific type

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

· Flammability

Not applicable.

· Lower and upper explosion limit· Lower:

1.2 Vol %

· Upper:

13 Vol %

· Flash point:

Not applicable, as aerosol.

· Ignition temperature:

333 °C

· Decomposition temperature:

Not determined.

· pH

Not determined.

Not applicable

· Viscosity:· Kinematic viscosity

Not determined.

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 8)

· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure at 20 °C:</u>	8,300 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.8 g/cm <sup>3</sup>
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.

**9.2 Other information**

· <u>Appearance:</u>	
· <u>Form:</u>	Aerosol
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	In use, may form flammable/explosive vapour-air mixture.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	82.0 %
· <u>Change in condition</u>	
· <u>Evaporation rate</u>	Not applicable.

## Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	
	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	
	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	
	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.

(Contd. on page 10)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name:** Interior Paint

(Contd. of page 9)

· **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.

\* **SECTION 11: Toxicological information**

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Dermal	LD50	73,333 mg/kg
Inhalative	LC50/4 h	233-246 mg/l (rat)

**67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat)
		7,426-15,800 mg/kg (rbt)
Inhalative	LC50/4 h	76 mg/l (rat)
	NOAEL	22,500 mg/m <sup>3</sup> (rat)
	LC50/48h	8,450 mg/l (cru) 2,262 mg/l (daphnia magna)

**123-86-4 n-butyl acetate**

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	>14,112 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	23.4 mg/l (rat) (OECD 403)
	LC50	390 mg/m <sup>3</sup> (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

**74-98-6 propane**

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

**106-97-8 butane, pure**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	LD50	6,190 mg/kg (rat) (OECD 401)
	NOAEL-Werte	1,500 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
		>2,000 mg/kg (rat)
Inhalative	LC50/4h	>10,000 mg/m <sup>3</sup> (rat)
	LC50	>23.8 mg/l (rat)
	LC50/4 h	35.7 mg/l (rat)
	LC50/48h	100 mg/l (Desmodesmus subspicatus)

**reaction mass of ethylbenzole and xylene**

Oral	LD50	3,523 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat)
Dermal	LD50	12,126 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m <sup>3</sup> (rat)
	LC50/4 h	27.124 mg/l (rat)

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 10)

**13463-67-7 titanium dioxide**

Oral	LD50	>5,010 mg/kg (rat)
	NOAEL	24,000 mg/kg (rat)
Dermal	LD50	>10,010 mg/kg (rbt)
	NOAEL	10 mg/m <sup>3</sup> (rat)
Inhalative	LC50/48h	>100 mg/l (daphnia magna)

**64-17-5 ethanol**

Oral	LD50	10,470 mg/kg (rat) (OECD 401)
	NOAEL-Werte	>3,000 mg/kg (rat) (OECD 451)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
	LC50/4h	20,000 mg/m <sup>3</sup> (rat)
Inhalative	LC50/4 h	120 mg/l (rat) (OECD 403)
	LC50/48h	5,012 mg/l (ceriodaphnia Dubai)
		12,340 mg/l (daphnia magna)
		8,150 mg/l (Leuciscus idus)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

- Endocrine disrupting properties
- None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

- Aquatic toxicity:

**67-64-1 acetone**

EC50/96h	7,200 mg/l (green alge)
	8,300 mg/l (piscis)
	8,300 mg/l (lepomis macrochirus)
	7,500 mg/l (selenastrum capricornutum)
EC50	1,700 mg/l (bacteria)
	6,368 mg/l (piscis)
EC5/16h	1,700 mg/l (pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (Microcystis aeruginosa)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
	3,400 mg/l (green alge)
EC50/48h	8,800 mg/l (daphnia magna)
	1,700 mg/kg (pseudomonas putida)
NOEC	4,740 mg/kg (selenastrum capricornutum)

(Contd. on page 12)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 11)

NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.)
	8,800 mg/l (daphnia magna)
LC50/96h	8,300 mg/l (lem)
	8,300 mg/l (Iepomis macrochirus)
	7,500 mg/l (Leuciscus idus)
	5,540 mg/l (Oncorhynchus mykiss)
	8,120 mg/l (Pimephales promelas)

**123-86-4 n-butyl acetate**

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna) (OECD 211)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)
	674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.)
	81 mg/l (piscis)
	100 mg/l (Iepomis macrochirus)
	62 mg/l (Leuciscus idus) (DIN 38412)
	18 mg/l (pimephales promelas) (OECD 203)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50	>100 mg/l (daphnia magna)
LC50	63.5 mg/l (Oryzias latipes)
EC50/48h	>500 mg/l (daphnia magna) (RL 67/548/EWG. Anhang V, C.2.)
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC20/0.5h	>1,000 mg/l (BES) (OECD 209)
NOEC	47.5 mg/l (Oryzias latipes)
NOEC/21d	≥100 mg/l (daphnia magna)
EC10	>1,000 mg/l (BES)
LC50/96h	180 mg/l (Oncorhynchus mykiss)
	>1,000 mg/l (Oryzias latipes)
	161 mg/l (Pimephales promelas)

**reaction mass of ethylbenzole and xylene**

LC50/24h	1 mg/l (daphnia magna) (OECD 202)
EC50/48h	3.2-9.5 mg/l (daphnia magna) (US EPA)
ErC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC	16 mg/l (BES)
	1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (green alge)
NOEC/21d	1.57 mg/l (daphnia magna) (OECD 211)

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 12)

NOELR/28d	16 mg/l (bacteria)
EC50/72h	2.2 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss) (OECD 203)
	8.9-16.4 mg/l (pimephales promelas)

**13463-67-7 titanium dioxide**

EC50	>1,000 mg/l (bacteria)
EC50/48h	>100 mg/l (daphnia magna)
EC50/72h	16 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	>1,000 mg/l (pimephales promelas)

**64-17-5 ethanol**

LC50/24h	11,200 mg/l (Salmo gairdneri)
EC50/48h	9,268-14,221 mg/l (daphnia magna)
	12,900 mg/l (Selenastrum capricornutum) (OECD 201)
EC0	6,500 mg/l (pseudomonas putida)
	5,000 mg/l (scenedesmus quadricauda)
EC10	11.5 mg/l (CHV)
EC50/72h	275 mg/l (CHV) (OECD 201)
LC50/96h	13,000 mg/l (Oncorhynchus mykiss) (OECD 203)
	15,300 mg/l (pimephales promelas)
	11,200 mg/l (Salmo gairdneri) (US EPA method E03-05)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- PBT: Not applicable.

- vPvB: Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- Additional ecological information:

- General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish

(Contd. on page 14)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 13)

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging

· Uncleaned packaging:· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

**SECTION 14: Transport information**· **14.1 UN number or ID number**· ADR, IMDG, IATA

UN1950

· **14.2 UN proper shipping name**· ADR

1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· ADR· Class

2 5F Gases.

· Label

2.1

· IMDG, IATA· Class

2.1 Gases.

· Label

2.1

· **14.4 Packing group**· ADR, IMDG, IATA

Void

· **14.5 Environmental hazards:**· Marine pollutant:

No

· **14.6 Special precautions for user**· Hazard identification number (Kemler code):

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

(Contd. on page 15)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name: Interior Paint**

(Contd. of page 14)

·	Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· Transport/Additional information:	
· <u>ADR</u>	
· <u>Limited quantities (LQ)</u>	1L
· <u>Excepted quantities (EQ)</u>	Code: E0 Not permitted as Excepted Quantity
· <u>Transport category</u>	2
· <u>Tunnel restriction code</u>	D
· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	1L
· <u>Excepted quantities (EQ)</u>	Code: E0 Not permitted as Excepted Quantity
· <u>UN "Model Regulation":</u>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

3

· National regulations:

- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.  
Employment restrictions concerning juveniles must be observed.

(Contd. on page 16)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 9 (replaces version 8)

Revision: 12.01.2023

**Trade name:** Interior Paint

(Contd. of page 15)

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 694.4 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory

· Date of previous version: 18.01.2022

· Version number of previous version: 8

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 1: Flammable liquids – Category 1  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Sol. 1: Flammable solids – Category 1  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1

EU