

e-mail info@akemi.de

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• <u>Trade name:</u> <u>Stone and Marble Adhesive-MS76 knifegrade</u>

· <u>Article number:</u> 10915, 10917, 10919, 10921, 10922, 10923

• UFI: AU20-V0J5-E00N-NWQ8
• 1.2 Relevant identified uses of

1.2 Relevant identified uses of the substance or mixture and

uses advised againstNo further relevant information available.

· Application of the substance / the

<u>mixture</u> Polyester resin adhesive

· 1.3 Details of the supplier of the safety data sheet

• <u>Manufacturer/Supplier:</u> AKEMI chemisch technische Spezialfabrik GmbH Lechstrasse 28 Tel. +49(0)911-642960 Fax. +49(0)911-644456

Lechstrasse 28 D 90451 Nürnberg

· Further information obtainable

from: Laboratory

· 1.4 Emergency telephone

<u>number:</u> Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 The

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.







GHS02 GHS07 GHS08

· <u>Signal word</u> Danger

· Hazard-determining components of

labelling: styrene

· Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated

exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

P102 Keep out of reach of children.

(Contd. on page 2)



Page 2/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

(Contd. of page 1)

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P260 Do not breathe vapours.

P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P314 Get medical advice/attention if you feel unwell. P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.∨PvB: Not applicable.

· Determination of endocrine-

disrupting properties For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-25%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40-0000	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
CAS: 130-15-4 EINECS: 204-977-6 Reg.nr.: 01-2120760462-57	1,4-naphthoquinone Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 1, H330 Skin Corr. 1C, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Skin Sens. 1, H317; STOT SE 3, H335	<1%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

(Contd. on page 3)



Page 3/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 2)

· After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

and effects, both acute and delayed

Headache Dizziness Dizziness

Breathing difficulty Profuse sweating

Nausea

· <u>Hazards</u> Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special

treatment needed If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

· For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· <u>Protective equipment:</u> Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

· Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage

system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



(Contd. of page 3)

Page 4/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than

air).

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and

explosion protection: Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle. Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class:

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that

require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

Oral DNEL (Langzeit-wiederholt) 2.1 mg/kg bw/day (BEV) Dermal DNEL (Langzeit-wiederholt) 406 mg/kg bw/day (ARB) Inhalative DNEL (Kurzzeit-akut) 289-306 mg/m³ Air (ARB) DNEL (Langzeit-wiederholt) 406 mg/kg bw/day (ARB) 343 mg/kg bw/day (BEV) 289-306 mg/m³ Air (ARB) 174.25-182.75 mg/m³ Air (BEV) BNEL (Langzeit-wiederholt) 85 mg/m³ Air (ARB)

(Contd. on page 5)



Page 5/13

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3) Printing date 20.11.2023 Revision: 20.11.2023

		and Marble Adhesive	
			10.2 mg/m³ Air (BEV) (Contd. of page
7770 00 0	4vi=in	a bia/arthanhaanhata	,
		c bis(orthophosphate	,
		, ,	0.83 mg/kg bw/day (BEV)
Dermal	DNEL	. (Langzeit-wiedernoit)	83 mg/kg bw/day (ARB)
La la al a Cara	DAIEI	/I 24 2 I	83 mg/kg bw/day (BEV)
innalative	DNEL	(Langzeit-wiederholt)	5 mg/m³ Air (ARB)
100 17 1 1		1.41	2.5 mg/m³ Air (BEV)
	-	phthoquinone	0.033 mg/m³ Air (ARB)
	DINLL	(Langzen-wiedenion)	0.000 Highii Ali (AND)
PNECs			
100-42-5 s	-		
PNEC (was	ssrig)	5 mg/l (KA)	
		0.014 mg/l (MW)	
		0.028 mg/l (SW)	
D. 150 //	4)	0.04 mg/l (WAS)	(0.0)
PNEC (fes	it)	0.2 mg/kg Trockengev	
		0.307 mg/kg Trockeng	
100 15 : :		0.614 mg/kg Trockeng	gew (SVVS)
	-	phthoquinone	
PNEC (wä	ssrig)	0.172 mg/l (KA)	
		0.00261 mg/l (MW)	
		0.0261 mg/l (SW)	
PNEC (fes	it)	0.049 mg/kg Trockeng	
		0.0321 mg/kg Trocken	
		0.321 mg/kg Trockeng	
Additional	inform	ation: The	e lists valid during the making were used as basis.
8.2 Expos	ure co		
Appropriate	e engi		further data; see section 7.
Individual p	protect	tion measures, such as ve and hygienic	personal protective equipment
measures:		<u>re and riygienic</u> Apr	oly solvent resistant skin cream before starting work.
	-		not eat, drink, smoke or sniff while working.
		Use	e skin protection cream for skin protection.
K Ir W D			an skin thoroughly immediately after handling the product.
			ep away from foodstuffs, beverages and feed. nediately remove all soiled and contaminated clothing
			sh hands before breaks and at the end of work.
		Do	not inhale gases / fumes / aerosols.
			oid contact with the eyes and skin.
Respiratory protection:			ort term filter device: er A/P2
li ii			ease of brief exposure or low pollution use respiratory filter device. In case
		inte	nsive or longer exposure use self-contained respiratory protective device.
	Hand protection		ventive skin protection by use of skin-protecting agents is recommended.
Hand prote	ection		er use of gloves apply skin-cleaning agents and skin cosmetics.
Hand prote	<u>ection</u>	Afte	
Hand prote	<u>ection</u>	Afte Skir	n protection agent recommendation for preventive skin shelter without use
Hand prote	ection	Afte Skir prof	n protection agent recommendation for preventive skin shelter without use tective gloves:
Hand prote	ection	Afte Skir prof ARI Skir	n protection agent recommendation for preventive skin shelter without use

Page 6/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 5)

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

SOLOPOL (http://www.stoko.com) Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level < 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890) Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)


Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· Not suitable are gloves made of the following materials:

Chloroprene rubber, CR Natural rubber, NR Rubber gloves

Eye/face protection



(Contd. on page 7)



Page 7/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 6)

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

General Information

· Colour: Different according to colouring · Odour: Characteristic · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 145 °C

· Lower and upper explosion limit

1.2 Vol % · Lower: 8.9 Vol % · Upper: · Flash point: 31 °C · Auto-ignition temperature: 480 °C

Not determined. · pH

Not applicable

· Viscosity:

· Kinematic viscosity Not determined.

Not applicable 55,000 mPas

· Dynamic at 20 °C:

· Solubility

Not miscible or difficult to mix. · water:

· Vapour pressure at 20 °C: 6 hPa

Density and/or relative density

Density at 20 °C: 1.79 g/cm³

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and

environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of explosive Explosive properties:

air/vapour mixtures are possible.

· Solvent content:

14.5 % · Organic solvents: 84.8 % Solids content:

· Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in

contact with water Void Void Oxidising liquids · Oxidising solids Void Void

· Organic peroxides

(Contd. on page 8)



Page 8/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 7)

Corrosive to metalsDesensitised explosivesVoid

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions

Exothermic polymerisation.

Reacts with peroxides and other radical forming substances.

Reacts with strong acids. Reacts with strong alkali.

Reacts with strong alkali.
Reacts with strong oxidising agents.

· 10.4 Conditions to avoid · 10.5 Incompatible materials: No further relevant information available. No further relevant information available.

10.6 Hazardous decomposition

products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 81.4 mg/l (rat)

100-42-5	styrene
Oral	LD50

Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m3 (mouse)
		11,800 mg/m3 (rat)

>2,000 mg/kg (rat)

LC50/4 h 11.8 mg/l (rat)
NOAEC 4.34 mg/l (rat)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.7 mg/l (rat)

130-15-4 1,4-naphthoquinone

Oral	LD50	124 mg/kg (rat)
	NOAEL-Werte	
Dermal		300 mg/kg (ATE)
	LD50	202 mg/kg (rat)
Inhalative	LC50/4h	46 mg/m3 (rat)
	LC50/4 h	0.005 mg/l (ATE)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation · Germ cell mutagenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

CarcinogenicityReproductive toxicity

Based on available data, the classification criteria are not met. Suspected of damaging the unborn child.

(Contd. on page 9)



Page 9/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 8)

· STOT-single exposure

Based on available data, the classification criteria are not met.

· STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
100-42-5 st	100-42-5 styrene		
EC50/96h 6.3 mg/l (Pseudokirchneriella subcapitata)			
EC50 500 mg/l (BES) (ISO Vorschrift 8192-1986 E)			
	5.5 mg/l (Photobac. phosphoreum)		
IC50/72h	4.9 mg/l (algae)		
	1.4 mg/l (selenastrum capricornutum)		
IC5/8d	>200 mg/l (Scenedesmus quadricauda)		
EC10/16h	72 mg/l (pseudomonas putida)		
EC50/16h	>72 mg/l (pseudomonas putida)		
EC50/8d	>200 mg/l (Scenedesmus quadricauda)		
EC50/72u	>1-<10 mg/l (algae)		
EC20/0.5h	140 mg/l (BES) (OECD 209)		
NOEC/21d	1.01 mg/l (daphnia magna)		
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)		
EC50/48h	0.56 mg/l (algae)		
	3.3-7.4 mg/l (daphnia magna)		
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	>1-<10 mg/l (piscis)		
	19.03-33.53 mg/l (lem)		
3.24-4.99 mg/l (pimephales promelas)			
6.75-14.5 mg/l (Pimephales promelas)			
58.75-95.32 mg/l (poecilia reticulata)			
LC50/72h	4.9 mg/l (algae)		
7779-90-0 trizinc bis(orthophosphate)			
EC50/48h	28.2 mg/l (daphnia magna)		
ErC50/72h	<0.3 mg/l (Desmodesmus subspicatus)		
EC50/48h	<1.7 mg/l (daphnia magna)		
EC50/72h	0.28 mg/l (Selenastrum capricornutum)		
LC50/96h	<5.1 mg/l (Oncorhynchus mykiss)		
130-15-4 1,4-naphthoquinone			
NOEC	0.011 mg/kg (algae)		
	0.026 mg/l (daphnia magna)		
EC50/72h	0.011 mg/l (algae)		
	0.42 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	0.045 mg/l (Oryzias latipes)		
	(Contd. on page 10		

EU



Page 10/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 9)

· 12.2 Persistence and

No further relevant information available. degradability No further relevant information available. · 12.3 Bioaccumulative potential 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Remark:

Harmful to fish

· Additional ecological information:

Do not allow product to reach ground water, water course or sewage system. · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Must not be disposed together with household garbage. Do not allow product to · Recommendation

reach sewage system.

• •		
· European waste catalogue		
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS	
20 01 00	separately collected fractions (except 15 01)	
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	packaging (including separately collected municipal packaging waste)	

· Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR IMDG IATA	UN3269

14.2 UN proper shipping name

· ADR 3269 POLYESTER RESIN KIT · IMDG, IATA POLYESTER RESIN KIT

15 01 10* packaging containing residues of or contaminated by hazardous substances

14.3 Transport hazard class(es)

· ADR



Class 3 (F3) Flammable liquids.

(Contd. on page 11)



Page 11/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 10)

3 · Label

IMDG, IATA



3 Flammable liquids. · Class

Label

· 14.4 Packing group

· ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

· Marine pollutant: Nο

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

· EMS Number: F-E,S-D · Stowage Category

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category · Tunnel restriction code Ε

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: See SP340

· UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed. · Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the

application of lower-tier

requirements 5,000 t

· Qualifying quantity (tonnes) for the

application of upper-tier

50,000 t

requirements · REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 4 (replaces version 3) Revision: 20.11.2023

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 11)

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

Water hazard class 2 (Self-assessment): hazardous for water. · Waterhazard class:

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 259.4 g/l

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS:

Laboratory

· Contact:

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

· Date of previous version:

15.03.2022

· Version number of previous

version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3

(Contd. on page 13)



Page 13/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.11.2023

Version number 4 (replaces version 3)

Trade name: Stone and Marble Adhesive-MS76 knifegrade

(Contd. of page 12)

Revision: 20.11.2023

Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3