

	according to 1907/2006/EC, Article 31	
Printing date 20.12.2023	Version number 5 (replaces version 4)	Revision: 20.12.2023
SECTION 1: Identification of the	substance/mixture and of the company/undertaking	
• <u>1.1 Product identifier</u> • Trade name:	Marble Filler 1000 THIXO	
· <u>Article number:</u> · UFI:	10417, 10418, 10422, 10423, 10424, 10425, 10426 10431, 10432, 10435, 10436, 10438, 10439 TDA4-80YA-N00T-2WF3	5, 10427, 10428, 10430,
• 1.2 Relevant identified uses of the substance or mixture and	1044-0014-10001-20013	
uses advised against Application of the substance / the	No further relevant information available.	
mixture	Knife filler/ Surfacer	
 <u>1.3 Details of the supplier of the</u> Manufacturer/Supplier: 	<u>safety data sheet</u> AKEMI chemisch technische Spezialfabrik GmbH Lechstrasse 28 D 90451 Nürnberg	Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de
 Further information obtainable from: 1.4 Emergency telephone 	Laboratory	
number:	Product Safety Department AKEMI chemisch technisch Tel. +49(0)911-64296-59 Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m. Friday from 07:30 a.m. to 13:30 p.m.	e Spezialfabrik GmbH
SECTION 2: Hazards identificati	on	
• 2.1 Classification of the substan • Classification according to Regula		
	ible liquid and vapour.	
Skin Irrit. 2 H315 Causes	skin irritation.	
Eye Irrit. 2 H319 Causes	serious eye irritation.	
Skin Sens. 1 H317 May cau	use an allergic skin reaction.	
Repr. 2 H361d Suspect	ed of damaging the unborn child.	
STOT RE 2 H373 May cau	use damage to the hearing organs through prolonged or re	epeated exposure.
Aquatic Chronic 3 H412 Harmful	to aquatic life with long lasting effects.	
 <u>2.2 Label elements</u> <u>Labelling according to Regulation</u> (EC) No 1272/2008 <u>Hazard pictograms</u> 	The product is classified and labelled according to the C	CLP regulation.
	GHS02 GHS07 GHS08	
· Signal word	Warning	
· Hazard-determining components of		
labelling:	styrene	
· <u>Hazard statements</u>	 maleic anhydride Reaction mass of 2,2'-[(4-methylphenyl)imino]bi hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. 	sethanol and 2-[[2-(2-
	, , , , , , , , , , , , , , , , , , , ,	(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO (Contd. of page 1) H361d Suspected of damaging the unborn child. H373 May cause damage to the hearing organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. H412 · Precautionary statements P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children. P102 P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapours. Wear protective gloves / eye protection. P280 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/attention if you feel unwell. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep cool. P403+P235 Dispose of contents/container in accordance with local/ P501 regional/national/international regulations. · 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · Determination of endocrinedisrupting properties For information on endocrine disrupting properties see section 11. **SECTION 3: Composition/information on ingredients** · 3.2 Mixtures · Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 100-42-5 <10% styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 EINECS: 202-851-5 Index number: 601-026-00-0 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, Reg.nr.: 01-2119457861-32 H335 Aquatic Chronic 3, H412 CAS: 25013-15-4 vinyltoluene 1-5% EINECS: 246-562-2 Flam. Liq. 3, H226 Reg.nr.: 01-2119622074-50-0000 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 EC number: 911-490-9 Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-<1% hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol Reg.nr.: 01-2119979579-10

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

	(Co	ntd. of page 2)
CAS: 108-31-6	maleic anhydride	<1%
EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31	Resp. Sens. 1, H334; STOT RE 1, H372 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 EUH071 Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.001$ %	
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:	Take affected persons out into the fresh air.
	Position and transport stably in side position.
	Symptoms of poisoning may even occur after several hours; therefore medical
	observation for at least 48 hours after the accident.
 After inhalation: 	Supply fresh air. If required, provide artificial respiration. Keep patient warm.
	Consult doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for
	transportation.
· <u>After skin contact:</u>	If skin irritation continues, consult a doctor.
	Immediately wash with water and soap and rinse thoroughly.
· <u>After eye contact:</u>	Rinse opened eye for several minutes under running water. If symptoms persist,
	consult a doctor.
· <u>After swallowing:</u>	If symptoms persist consult doctor.
4.2 Most important symptoms	
and effects, both acute and	
delayed	Headache
	Dizziness
	Dizziness
	Nausea
· <u>Hazards</u>	Danger of impaired breathing.
• 4.3 Indication of any immediate	
medical attention and special	
treatment needed	If swallowed, gastric irrigation with added, activated carbon.
SECTION 5: Firefighting measur	es
• 5.1 Extinguishing media	
· Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol
	resistant foam

	resistant toam.
 For safety reasons unsuitable 	
extinguishing agents:	Water with full jet
5.2 Special hazards arising fron	1
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
	In case of fire, the following can be released:
	Carbon monoxide (CO)
	Nitrogen oxides (NOx)
	Under certain fire conditions, traces of other toxic gases cannot be excluded,
	e.g.:
	Hydrogen cyanide (HCN)
5.3 Advice for firefighters	
· Protective equipment:	Wear self-contained respiratory protective device.
	Do not inhale explosion gases or combustion gases.
	Wear fully protective suit.
	Mount respiratory protective device.
	(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 20.12.2023 Version number 5 (replaces version 4) Revision: 20.12.2023 Trade name: Marble Filler 1000 THIXO (Contd. of page 3) Dispose of fire debris and contaminated fire fighting water in accordance with · Additional information official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system. **SECTION 6: Accidental release measures** 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Do not allow product to reach sewage system or any water course. · 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Dispose of the material collected according to regulations. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. See Section 7 for information on safe handling. · 6.4 Reference to other sections See Section 8 for information on personal protection equipment. See Section 13 for disposal information. SECTION 7: Handling and storage · 7.1 Precautions for safe handling Keep receptacles tightly sealed. Store in cool, dry place in tightly closed receptacles. Keep away from heat and direct sunlight. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Store only in the original receptacle. Prevent any seepage into the ground. · Information about storage in one common storage facility: Store away from oxidising agents. Store away from foodstuffs. · Further information about storage Store receptacle in a well ventilated area. conditions: Keep container tightly sealed. · Storage class: 3 · 7.3 Specific end use(s) No further relevant information available.

- EU



Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

		(Contd. of page
SECTION	8: Exposure controls/perso	onal protection
	<u>ol parameters</u> s with limit values that require	monitoring at the workplace:
	ethyl acetate	
	nort-term value: 1468 mg/m ³ , 4	100 ppm
	ong-term value: 734 mg/m ³ , 20	
DNELs		
100-42-5 \$	styrene	
Oral	-	2.1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	406 mg/kg bw/day (ARB)
		343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m³ Air (ARB)
		174.25-182.75 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	85 mg/m³ Air (ARB)
	, , , , , , , , , , , , , , , , , , , ,	10.2 mg/m ³ Air (BEV)
25013-15-	4 vinyltoluene	
Oral	-	0.0833 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	
	, , , , , , , , , , , , , , , , , , , ,	0.595 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5.83 mg/m ³ Air (ARB)
	(g,	1.04 mg/m ³ Air (BEV)
		yl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)
amino]-et		
Oral	(e /	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	
		0.83 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	9.8 mg/m³ Air (ARB)
		2.9 mg/m³ Air (BEV)
	ethyl acetate	
Oral	DNEL (Langzeit-wiederholt)	
Dermal	DNEL (Langzeit-wiederholt)	
		37 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,468 mg/m³ Air (ARB)
		734 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	734 mg/m³ Air (ARB)
		367 mg/m³ Air (BEV)
	maleic anhydride	
Oral	DNEL (Langzeit-wiederholt)	0.06 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.04 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	
		0.1 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	0.8 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.4 mg/m³ Air (ARB)
		0.08 mg/m³ Air (BEV)
		(Contd. on page

(Contd. on page 6) EU



- EU -

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

	(Contd. of page 5)				
· <u>PNECs</u>					
100-42-5 styren					
PNEC (wässrig)	5 mg/l (KA)				
	0.014 mg/l (MW)				
	0.028 mg/l (SW)				
	0.04 mg/l (WAS)				
PNEC (fest)	0.2 mg/kg Trockengew (BO)				
	0.307 mg/kg Trockengew (MWS)				
	0.614 mg/kg Trockengew (SWS)				
25013-15-4 viny	Itoluene				
PNEC (wässrig)	17 mg/l (KA)				
	0.000319 mg/l (MW)				
	0.0000319 mg/l (SW)				
PNEC (fest)	0.00471 mg/kg Trockengew (BO)				
	0.025 mg/kg Trockengew (MWS)				
	1.245 mg/kg Trockengew (SWS)				
	of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)				
amino]-ethanol					
PNEC (wässrig)	• • •				
	0.005 mg/l (MW)				
	0.048 mg/l (SW)				
PNEC (fest)	0.21 mg/kg Trockengew (BO)				
	0.12 mg/kg Trockengew (MWS)				
	1.2 mg/kg Trockengew (SWS)				
141-78-6 ethyl a					
PNEC (wässrig)					
	0.024 mg/l (MW)				
	0.24 mg/l (SW)				
	1.65 mg/l (WAS)				
PNEC (fest)	0.148 mg/kg Trockengew (BO)				
	0.115 mg/kg Trockengew (MWS)				
	1.15 mg/kg Trockengew (SWS)				
108-31-6 maleic	anhydride				
PNEC (wässrig)	44.6 mg/l (KA)				
	0.0043 mg/l (MW)				
	0.043 mg/l (SW)				
	0.4281 mg/l (WAS)				
PNEC (fest)	0.042 mg/kg Trockengew (BO)				
	0.0334 mg/kg Trockengew (MWS)				
	0.334 mg/kg Trockengew (SWS)				
· Additional inform	ation: The lists valid during the making were used as basis.				
· 8.2 Exposure co	ontrols				
 Appropriate engi 	neering controls No further data; see section 7.				
	tion measures, such as personal protective equipment				
· General protectiv					
measures:	Do not eat, drink, smoke or sniff while working. (Contd. on page 7)				



Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

	(Contd of nora 6)
	(Contd. of page 6) Use skin protection cream for skin protection.
	Be sure to clean skin thoroughly after work and before breaks.
	Keep away from foodstuffs, beverages and feed.
	Immediately remove all soiled and contaminated clothing
	Wash hands before breaks and at the end of work.
	Store protective clothing separately.
	Do not inhale gases / fumes / aerosols.
	Avoid contact with the eyes and skin.
 Respiratory protection: 	Filter A/P2
	In case of brief exposure or low pollution use respiratory filter device. In case of
	intensive or longer exposure use self-contained respiratory protective device.
· Hand protection	Preventive skin protection by use of skin-protecting agents is recommended.
	After use of gloves apply skin-cleaning agents and skin cosmetics.
	Skin protection agent recommendation for preventive skin shelter in application
	and combination of protective gloves:
	STOKO EMULSION (http://www.stoko.com)
	Skin protection recommendation for skin cleaning after product handling: SOLOPOL (http://www.stoko.com)
	Kresto Classic (http://debstoko.com)
	Skin protection agent recommendation for skin aftercare:
	STOKO VITAN (http://www.stoko.com)
	The protection gloves to be used have to comply with the specifications of the
	directive 89/686/EC and the directive derived decree EN374, respectively, e.g.
	the above listed protection glove type. The mentioned permeation times' data
	were generated and verified with material samples of the recommended
	protection glove type in the scope of laboratory anylyses of the company KCL
	GmbH in compliance with EN374.
	This recommendation refers exclusively to the material safety data sheet
	referenced product delivered by Akemi and the indicated field of application. In
	case of product dilution or in case of mixture with different substances or
	chemicals, and in condition of EN374 deviation the producer of CE-approved
	protection gloves must be contacted for detailed information (e.g., KCL GmbH,
	Germany, 36124 Eichenzell, internet: http://www.kcl.de).
	Protective gloves
	The glove material has to be impermeable and resistant to the product/
	the substance/ the preparation.
	Due to missing tests no recommendation to the glove material can be
	given for the product/ the preparation/ the chemical mixture.
	Selection of the glove material on consideration of the penetration
	times, rates of diffusion and the degradation
 Material of gloves 	Butyl rubber, BR
	The selection of the suitable gloves does not only depend on the material, but
	also on further marks of quality and varies from manufacturer to manufacturer.
	As the product is a preparation of several substances, the resistance of the glove
	material can not be calculated in advance and has therefore to be checked prior
Demotration time of allowed to be	to the application.
· Penetration time of glove material	Value for the permeation: Level \leq 1, 30 min
	The exact break trough time has to be found out by the manufacturer of the
. For the permanent contact douce	protective gloves and has to be observed.
 For the permanent contact gloves made of the following materials are 	
suitable:	Butyl rubber, BR
Sulade.	Butoject (KCL, Art_No. 897, 898)
	(Contd. on page 8)
	EU-



Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

. As protection from splashes aloves		(Contd. of page 7)
 As protection from splashes gloves made of the following materials are 		
suitable:	Butyl rubber, BR	
· Not suitable are gloves made of	Butoject (KCL, Art_No	p. 897, 898)
the following materials:	Fluorocarbon rubber	(Viton)
	Chloroprene rubber, (
	Natural rubber, NR	_
	Strong material glove Leather gloves	S
	Nitrile rubber, NBR	
· Eye/face protection		
	Tightly seal	ed goggles
· Body protection:	Protective work clothi	ng
SECTION 9: Physical and chemic	cal properties	
• 9.1 Information on basic physica	· ·	rties
· General Information		
· Colour:		Different according to colouring
 <u>Odour:</u> Melting point/freezing point: 		Characteristic Undetermined.
· Boiling point or initial boiling point a	nd boiling range	145 °C
· Lower and upper explosion limit	V	
· Lower:		1.2 Vol % 8.9 Vol %
· <u>Upper:</u> · Flash point:		32 °C
· Auto-ignition temperature:		480 °C
· <u>pH</u>		Not determined.
· Viscosity:		Not applicable
· Kinematic viscosity		Not determined.
· Dynamic at 20 °C:		35,000 mPas
· <u>Solubility</u> · water:		Not miscible or difficult to mix.
· Vapour pressure at 20 °C:		6 hPa
Density and/or relative density		
· Density at 20 °C:		1.74 g/cm³ ([1,73 - 1,78 g/cm³])
9.2 Other information		
· <u>Appearance:</u> · Form:		Pasty
· Important information on prote	ection of health and	
environment, and on safety.		
Ignition temperature:		Product is not selfigniting.
· Explosive properties:		Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:		
· Organic solvents:		14.6 %
· <u>Solids content:</u>		82.6 %
 Information with regard to physical Explosives 	nazard classes	Void
· Flammable gases		Void
· Aerosols		Void
		(Contd. on page 9)



ΕU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

	(Contd. of page 8)
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
 Self-heating substances and mixtures 	Void
· Substances and mixtures, which emit flammable gases in	1
contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

 <u>10.1 Reactivity</u> 10.2 Chemical stability 	No further relevant information available.
Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous	
reactions	Exothermic polymerisation.
	Reacts with peroxides and other radical forming substances.
	Reacts with strong acids.
	Reacts with strong alkali.
 10.4 Conditions to avoid 	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
ATE (Acute Toxicity Estimates)			
Inhalative	Inhalative LC50/4 h 79.3 mg/l		
100-42-5	styrene		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)	
Inhalative	LC50/4h	9.5 mg/m3 (mouse)	
		11,800 mg/m3 (rat)	
	LC50/4 h	11.8 mg/l (rat)	
	NOAEC	4.34 mg/l (rat)	
25013-15-	25013-15-4 vinyltoluene		
Oral	LD50	3,375 mg/kg (rat)	
	NOAEL	600 mg/kg (rat)	
Dermal	LD50	4,585 mg/kg (rabbit)	
		(Contd. on page 10	



Page 10/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

		(Contd. of page	
Inhalative		>16,891 mg/m3 (rat)	
	LC50/4 h	11 mg/l (ATE)	
Reaction amino]-et		4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)	
- Oral	LD50	619 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
141-78-6 🤅	ethyl acetate		
Oral	LD50	4,100 mg/kg (mouse)	
		5,620 mg/kg (rat)	
		4,934 mg/kg (rabbit) (OECD 401)	
	NOAEL-Werte	900 mg/kg (rat)	
Dermal	LD50	>18,000 mg/kg (rabbit)	
Inhalative	LC50	58 mg/l (rat)	
	LC50/4 h	56 mg/l (rat)	
	LC50/1h	200 mg/l (rat)	
	LC50/8h	5.86 mg/l (rat)	
	LC50/48h	333 mg/l (Leuciscus idus)	
	naleic anhydri		
Oral	LD50	1,090-2,620 mg/kg (rabbit) (OECD 401)	
		400-480 mg/kg (rat)	
	LD50	2,620 mg/kg (rabbit)	
Inhalative		>4.35 mg/l (rat)	
	LC50/48h	138 mg/l (lem)	
	sion/irritation	Causes skin irritation.	
Serious ey Respirator	<u>ve damage/irrita</u> y or skin sensiti	tion Causes serious eye irritation. isation May cause an allergic skin reaction.	
Germ cell	mutagenicity	Based on available data, the classification criteria are not met.	
Carcinoge	nicity	Based on available data, the classification criteria are not met.	
	ive toxicity	Suspected of damaging the unborn child.	
	gle exposure eated exposure	Based on available data, the classification criteria are not met. May cause damage to the hearing organs through prolonged or repeat	
		exposure.	
Aspiration		Based on available data, the classification criteria are not met.	
	mation on othe		
	disrupting prop		
None of th	e ingredients is		
SECTION	12: Ecological	information	
<u>12.1 Toxic</u>	city		
Aquatic to:			
100-42-5 s	•		
EC50/96h		eudokirchneriella subcapitata)	
EC50		ES) (ISO Vorschrift 8192-1986 E)	
	5.5 ma/l (Ph	otobac, phosphoreum)	

5.5 mg/l (Photobac. phosphoreum)

IC50/72h 4.9 mg/l (algae) 1.4 mg/l (selenastrum capricornutum)

(Contd. on page 11)

EU



Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

Printing date 20.12.2023

	(Contd. of page 10)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)
EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (algae)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (algae)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)
	3.24-4.99 mg/l (pimephales promelas)
	6.75-14.5 mg/l (Pimephales promelas)
	58.75-95.32 mg/l (poecilia reticulata)
LC50/72h	4.9 mg/l (algae)
25013-15-4 v	•
EC50	2.6 mg/l (Bluegill.)
EC50/48h	9.3 mg/l (daphnia magna)
ErC50/72h	4.3 mg/l (Pseudokirchneriella subcapitata)
NOEC	0.563 mg/l (piscis)
NOELR/72h	1.6 mg/l (algae)
NOEC/21d	0.32 mg/l (daphnia magna)
	0.563 mg/l (piscis)
EC10	0.25 mg/l (Desmodesmus subspicatus)
EC50/72h	0.319 mg/l (Desmodesmus subspicatus)
	5.2 mg/l (Fathead minnow)
	2.6 mg/l (selenastrum capricornutum)
LC50/96h	5.2-23.4 mg/l (piscis)
	5.2 mg/l (pimephales promelas)
Reaction ma	ass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)
amino]-etha	
EC50/48h	48 mg/l (daphnia magna)
EC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Cyprinus carpio)
141-78-6 eth	
EC50/24h	2,300-3,090 mg/l (daphnia magna)
EC50/96h	220 mg/l (Pimephales promelas)
EC10/18h	2,900 mg/l (pseudomonas putida)
EC50/48h	610 mg/l (daphnia magna) (DIN 38412)
	5,600 mg/l (Scenedesmus subspicatus)
IC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC 0	29.3 mg/l (rat)
NOELR/72h	>100 mg/l (Desmodesmus subspicatus)
	(Contd. on page 12)
	EU



Page 12/15

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

Printing date 20.12.2023

(Contd. of page 11) NOEC/21d 2.4 mg/l (daphnia magna) EC10 2,900 mg/l (pseudomonas putida) EC50/48h 3,300 mg/l (Scenedesmus subspicatus) 1,800-3,200 mg/l (selenastrum capricornutum) EC50/72h LC50/96h 300-600 mg/l (Oncorhynchus mykiss) 230 mg/l (Pimephales promelas) 108-31-6 maleic anhydride EC50/24h 316-330 mg/l (daphnia magna) **EC50** 77 mg/l (daphnia magna) EC10/18h 44.6 mg/l (pseudomonas putida) EC50/48h 42.81 mg/l (daphnia magna) (OECD 202) ErC50/72h 74.35 mg/l (Pseudokirchneriella subcapitata) (OECD 201) NOELR/72h 150 mg/l (Pseudokirchneriella subcapitata) NOEC/21d 10 mg/l (daphnia magna) EC50/72h 29 mg/l (Desmodesmus subspicatus) 74.32 mg/l (Pseudokirchneriella subcapitata) >150 mg/l (Selenastrum capricornutum) LC50/96h 75 mg/l (lepomis macrochirus) 75 mg/l (Oncorhynchus mykiss) 12.2 Persistence and No further relevant information available. degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available. 12.4 Mobility in soil 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Endocrine disrupting The product does not contain substances with endocrine disrupting properties. properties 12.7 Other adverse effects · Additional ecological information: Do not allow product to reach ground water, water course or sewage system. · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND	
	INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS	
20 01 00	separately collected fractions (except 15 01)	
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	
· Uncleaned packaging:		

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 13)



Page 13/15

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4)

Revision: 20.12.2023

- EU

Trade name: Marble Filler 1000 THIXO

Printing date 20.12.2023

· Recommended cleansing agents: Alcohol	(Contd. of page 12)			
SECTION 14: Transport information				
· <u>14.1 UN number or ID number</u> · <u>ADR, IMDG, IATA</u>	UN3269			
 <u>14.2 UN proper shipping name</u> <u>ADR</u> <u>IMDG, IATA</u> 	3269 POLYESTER RESIN KIT POLYESTER RESIN KIT			
 <u>14.3 Transport hazard class(es)</u> <u>ADR</u> 				
· <u>Class</u> · <u>Label</u>	3 (FT3) Flammable liquids. 3			
· IMDG, IATA				
· <u>Class</u> · <u>Label</u>	3 Flammable liquids. 3			
· <u>14.4 Packing group</u> · <u>ADR, IMDG, IATA</u>	Ш			
 <u>14.5 Environmental hazards:</u> <u>Marine pollutant:</u> 	No			
 • 14.6 Special precautions for user • Hazard identification number (Kemler code): • EMS Number: • Stowage Category 	Warning: Flammable liquids. 30 F-E,S-D A			
 <u>14.7 Maritime transport in bulk according to IM</u> instruments 	IO Not applicable.			
· Transport/Additional information:				
· <u>ADR</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	5L Code: E0 Not permitted as Excepted Quantity			
 Transport category Tunnel restriction code Remarks: 	3 D/E Without hardener component: no dangerous goods < 450 l			
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml			
· <u>Remarks:</u>	Without hardener component: no dangerous goods < 30 I (Contd. on page 14)			



according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

	(Contd. of page 13)			
· IATA				
· <u>Remarks:</u>	Without hardener component: 3/III UN 1866 Resin Solution			
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III			
SECTION 15: Regulatory informa				
 <u>15.1 Safety, health and environm</u> 	ental regulations/legislation specific for the substance or mixture			
Directive 2012/18/EU				
Named dangerous substances - ANNEX I Seveso category	None of the ingredients is listed. P5c FLAMMABLE LIQUIDS			
Qualifying quantity (tonnes) for the application of lower-tier requirements	5,000 t			
• Qualifying quantity (tonnes) for the application of upper-tier requirements	50,000 t			
 REGULATION (EC) No 1907/2006 ANNEX XVII 	Conditions of restriction: 3			
 DIRECTIVE 2011/65/EU on the res equipment – Annex II 	striction of the use of certain hazardous substances in electrical and electronic			
None of the ingredients is listed.				
• REGULATION (EU) 2019/1148				
	VES PRECURSORS (Upper limit value for the purpose of licensing under Article			
None of the ingredients is listed.				
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS				
None of the ingredients is listed.				
· Regulation (EC) No 273/2004 on d	rug precursors			
None of the ingredients is listed.				
• Regulation (EC) No 111/2005 layin countries in drug precursors	g down rules for the monitoring of trade between the Community and third			
None of the ingredients is listed.				
· National regulations:				
	Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.			
· Waterhazard class:	Water hazard class 2 (Self-assessment): hazardous for water.			
· Substances of very high concern (S	SVHC) according to REACH, Article 57			
None of the ingredients is listed.				
· <u>VOC EU</u>	255.1 g/l			
15.2 Chemical safety				
assessment:	A Chemical Safety Assessment has not been carried out.			

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.



according to 1907/2006/EC, Article 31

Printing date 20.12.2023

Version number 5 (replaces version 4)

Revision: 20.12.2023

Trade name: Marble Filler 1000 THIXO

(Contd. of page 14) This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory · Date of previous version: 07.06.2022 · Version number of previous version: 4 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de · Abbreviations and acronyms: fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (RÈACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative ATE: Acute toxicity estimate values Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity - Category 2 STOT RE 1: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 ΕU