

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Superfast Volume Filler**

Article number: 11159

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Knife filler/ Surfacers

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960

Fax. +49(0)911-644456

e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

styrene

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 1)

· <u>Precautionary statements</u>	P101 P102 P103 P210 P260 P280 P303+P361+P353 P305+P351+P338 P312 P333+P313 P403+P233 P405 P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapours. Wear protective gloves / eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.
-----------------------------------	--	---

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

· PBT: Not applicable.

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients**· 3.2 Mixtures**· Description: Mixture: consisting of the following components.**· Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-25%
EC number: 911-490-9 Reg.nr.: 01-2119979579-10	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<1%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 2)

- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
 - Headache
 - Dizziness
 - Dizziness
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- Protective equipment: Mount respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 3)

- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from frost.
Keep container tightly sealed.
- Storage class: 3
- **7.3 Specific end use(s)** No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- DNELs

100-42-5 styrene

Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	406 mg/kg bw/day (ARB) 343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m ³ Air (ARB) 174.25-182.75 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	85 mg/m ³ Air (ARB) 10.2 mg/m ³ Air (BEV)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

Oral	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	1.4 mg/kg bw/day (ARB) 0.83 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	9.8 mg/m ³ Air (ARB) 2.9 mg/m ³ Air (BEV)

108-31-6 maleic anhydride

Oral	DNEL (Langzeit-wiederholt)	0.06 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.04 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	0.2 mg/kg bw/day (ARB) 0.1 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	0.8 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.4 mg/m ³ Air (ARB) 0.08 mg/m ³ Air (BEV)

- PNECs

100-42-5 styrene

PNEC (wässrig) 5 mg/l (KA)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 4)

PNEC (fest)	0.014 mg/l (MW) 0.028 mg/l (SW) 0.04 mg/l (WAS) 0.2 mg/kg Trockengew (BO) 0.307 mg/kg Trockengew (MWS) 0.614 mg/kg Trockengew (SWS)
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol	
PNEC (wässrig)	10 mg/l (KA) 0.005 mg/l (MW) 0.048 mg/l (SW)
PNEC (fest)	0.21 mg/kg Trockengew (BO) 0.12 mg/kg Trockengew (MWS) 1.2 mg/kg Trockengew (SWS)
108-31-6 maleic anhydride	
PNEC (wässrig)	44.6 mg/l (KA) 0.0043 mg/l (MW) 0.043 mg/l (SW) 0.4281 mg/l (WAS)
PNEC (fest)	0.042 mg/kg Trockengew (BO) 0.0334 mg/kg Trockengew (MWS) 0.334 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 5)

- Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye/face protection  Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- General Information
- Colour: Different according to colouring
- Odour: Specific type
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 145 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 1.2 Vol %
- Upper: 8.9 Vol %
- Flash point: 31 °C
- Auto-ignition temperature: >370 °C
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity Not determined.
- Dynamic at 20 °C: 42,000 mPas
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 6 hPa
- Density and/or relative density
- Density at 20 °C: 1.54 g/cm³
- Relative density Not determined.
- Vapour density Not determined.

9.2 Other information

- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent content:
- Organic solvents: 22.4 %
- Solids content: 71.2 %
- Change in condition
- Evaporation rate Not determined.

Information with regard to physical hazard classes

- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 6)

· <u>Flammable liquids</u>	Flammable liquid and vapour.
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	Exothermic polymerisation. Reacts with peroxides and other radical forming substances.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· <u>Acute toxicity</u>	Based on available data, the classification criteria are not met.

· <u>LD/LC50 values relevant for classification:</u>
--

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	52.7 mg/l (rat)
------------	----------	-----------------

100-42-5 styrene

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m ³ (mouse)
		11,800 mg/m ³ (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

Oral	LD50	619 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

108-31-6 maleic anhydride

Oral	LD50	1,090-2,620 mg/kg (rabbit) (OECD 401)
		400-480 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 7)

Inhalative	LC50/1h	>4.35 mg/l (rat)
	LC50/48h	138 mg/l (lem)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity**

- Aquatic toxicity:

100-42-5 styrene

EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)
	5.5 mg/l (Photobac. phosphoreum)
IC50/72h	4.9 mg/l (algae)
	1.4 mg/l (selenastrum capricornutum)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)
EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (algae)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (algae)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)
	3.24-4.99 mg/l (pimephales promelas)
	6.75-14.5 mg/l (Pimephales promelas)
	58.75-95.32 mg/l (poecilia reticulata)
LC50/72h	4.9 mg/l (algae)

Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

EC50/48h	48 mg/l (daphnia magna)
EC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Cyprinus carpio)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 8)

108-31-6 maleic anhydride

EC50/24h	316-330 mg/l (daphnia magna)
EC50	77 mg/l (daphnia magna)
EC10/18h	44.6 mg/l (pseudomonas putida)
EC50/48h	42.81 mg/l (daphnia magna) (OECD 202)
ErC50/72h	74.35 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOELR/72h	150 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	10 mg/l (daphnia magna)
EC50/72h	29 mg/l (Desmodesmus subspicatus)
	74.32 mg/l (Pseudokirchneriella subcapitata)
	>150 mg/l (Selenastrum capricornutum)
LC50/96h	75 mg/l (Iepomis macrochirus)
	75 mg/l (Oncorhynchus mykiss)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- PBT:

Not applicable.

- vPvB:

Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- Additional ecological information:

- General notes:

Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:

- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN number or ID number**

- ADR, IMDG, IATA

UN1866

- **14.2 UN proper shipping name**

- ADR

1866 RESIN SOLUTION

- IMDG, IATA

RESIN SOLUTION

(Contd. on page 10)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 9)

· 14.3 Transport hazard class(es)· ADR

· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG, IATA

· Class 3 Flammable liquids.
 · Label 3

· 14.4 Packing group· ADR, IMDG, IATA III**· 14.5 Environmental hazards:**· Marine pollutant: No**· 14.6 Special precautions for user**

· Hazard identification number (Kemler code): Warning: Flammable liquids.
 30
 · EMS Number: F-E, S-E
 · Stowage Category E

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:· ADR

· Limited quantities (LQ)
 · Excepted quantities (EQ)

5L
 Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· Transport category
 · Tunnel restriction code
 · Remarks:

3
 D/E
 Without hardener component: no dangerous goods < 450 l

· IMDG

· Limited quantities (LQ)
 · Excepted quantities (EQ)

5L
 Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 Without hardener component: no dangerous goods < 30 l

· Remarks:· IATA· Remarks: Without hardener component: 3/III UN 1866 Resin Solution· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2023

Version number 3 (replaces version 2)

Revision: 19.12.2023

Trade name: Superfast Volume Filler

(Contd. of page 11)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU