

for epoxy-based adhesives

## **Technical Data Sheet**

Page 1 of 1

Properties:	AKEMI <sup>®</sup> Coloring Concentrates liquid / Coloring Pastes are concentrates in different color shades. The products are characterized by the following properties:
	<ul> <li>easy coloring of epoxy-based adhesives</li> <li>the liquid consistency (of concentrates) makes it easier to mix with liquid products</li> <li>matching the color of the adhesive to many common stone colors</li> <li>balanced pigment concentration, thus easy adjustment of different color shades and high coverage</li> </ul>
	<ul> <li>extremely UV- and light-resistant pigments, i.e. no fading</li> <li>no deterioration of the properties of the colored adhesives</li> </ul>
Application Area:	AKEMI <sup>®</sup> Coloring Concentrates liquid / Coloring Pastes are used for coloring AKEPOX <sup>®</sup> fillers and adhesives. Thus, the color of the adhesive can be adjusted to the respective stone color.
Instructions for Use:	<ol> <li>Add maximum 5% of AKEMI<sup>®</sup> Coloring Concentrate liquid / Coloring Paste to the adhesive to be colored, depending on the color of the concentrate and the stone.</li> <li>Mix well until a homogenous shade of color is achieved.</li> </ol>
Special Notes:	<ul> <li>Use afin<sup>®</sup> Liquid Glove to protect your hands.</li> <li>Hardener to be added after the color had been adjusted.</li> <li>For proper waste disposal, the container must be completely emptied.</li> </ul>
Technical Data:	Colors: red, redbrown, white, black, ochre, green, brown, blue Coloring Concentrates: additionally beige, grey
Storage:	If stored in dry and cool condition (41-77°F) in its closed original container at least 3 years from production.
Health & Safety:	Read Safety Data Sheet before handling or using this product.
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.