

Technical Data Sheet

Page 1 of 1

- Properties:** AKEMI® Primer AP 20 is a 1-component primer for AKEMI® silicone sealants.
- Application Area:** AKEMI® Primer AP 20 is used to prime the joint edges before applying sealants to metallic substrates such as zinc, anodised and stainless steel. For indoor and outdoor use in wall, floor and ceiling joints to improve the adhesion of sealants.
- Instructions for use:**
1. Contact areas must be dry, clean and free of grease and dust.
 2. Apply with a brush on the clean and dry surface.
 3. Protect treated surfaces from humidity and dust.
 4. The sealant can be applied after an evaporation time of approx. 30 - 60 minutes.
- Special Notes:**
- For professional use only.
 - To avoid staining, do not apply the primer to visible surfaces.
 - Tools can be cleaned with AKEMI® Universal Thinner.
 - For proper waste disposal, the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Storage:** If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 6 months from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 03.24