

Technical Data Sheet

Page 1 of 1

Properties:	<p>AKEMI® Quartz Polish is a care product made of reactive silicone oils with lubricants and polishing agents. The product reacts with air humidity and thus develops a resistant surface protection. The product has been especially developed for quartz and is characterized by the following qualities:</p> <ul style="list-style-type: none">- removes dirt sticking on the surface- enhances the resistance of quartz surfaces- refreshes the surface gloss- non yellowing- weather-resistant- tack-free hardening- after hardening, the product is harmless to health upon contact with food products - certified by an external German testing institute
Application Area:	<p>AKEMI® Quartz Polish is suited for the care of kitchen countertops, counters or other quartz surfaces (such as Caesarstone®, Cambria®, Silestone®, Zodiaq® etc.) as well as ceramic stove tops.</p>
Instructions for Use:	<ol style="list-style-type: none">1. Clean surfaces thoroughly with AKEMI® Quartz Intensive Cleaner and allow them to dry.2. Shake before use.3. Apply a thin layer with a soft cloth.4. Allow to dry, then polish with a soft cloth or polishing wool.5. For regular cleaning and care AKEMI® Quartz Clean & Care is very well suited.6. Sufficient ventilation (approx. 2 - 3 days) is necessary when using the product in food areas.
Special Notes:	<ul style="list-style-type: none">- AKEMI® Quartz Polish is only suited for polished or smooth surfaces.- A slight colour enhancement may be possible.- For proper waste disposal, the container must be completely emptied.
Technical Data:	<p>Colour: milky white Density: approx. 0.79 g/cm³</p>
Storage:	<p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.</p>
Health & Safety:	<p>Read Safety Data Sheet before handling or using this product.</p>
Important Notice:	<p>The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.</p>

TDS 03.21