

Disinfectant Cleaner

Technical Data Sheet

Page 1 of 1

Properties:

AKEMI® Disinfectant Cleaner is a highly concentrated and therefore especially economic cleaner based on organic acids with non-ionic and cationic tensides and odorous substances. The product is free from phosphates and strong inorganic acids; the tensides contained are biodegradable in correspondence with the legal regulations for tensides.

Application Area:

AKEMI® Disinfectant Cleaner is suited to the regular cleaning of acidresistant natural and artificial stone, tiles and synthetic materials as well as glass and stainless steel in kitchens, swimming pools, toilets, shower and bathrooms. On account of its special formula, it is not detrimental to chrome fittings and separating shower walls made of aluminum. In order to ensure simple and economic use, the diluted solution can be filled up in a normal household spray bottle (please keep out of the reach of children).

Instructions for Use:

- 1. Apply undiluted or dilute with water up to a ratio of 1:50 (approx. 100 ml to 5 liter of water).
- 2. Allow the product to work for several minutes.
- 3. Rinse thoroughly with water.
- 4. Brilliance can be intensified by polishing.

Special Notes:

- Do not apply on synthetic materials which are not resistant to acids,
 s. a. polished marble or similar. If in doubt, test on an inconspicuous area.
 - For proper waste disposal, the container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data:

Coverage: approx. 10 - 20 m²/liter (if applied purely).

If diluted in a ratio of 1:50, the cleaner is sufficient for

approx. 500 - 1,000 m²

Colour: blue

Density: approx. 1.09 g/cm³

pH value: approx. 1

Storage:

If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.

Health & Safety: Read Safety Data Sheet before handling or using this product.

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 12.23