

## **Technical Data Sheet**

Page 1 of 1

Properties:	AKEMI <sup>®</sup> Stone Polish - wax based is a superior, polymer-strengthened wax emulsion which is free from solvents with a pleasant odour. Treated surfaces obtain a brilliant, but also anti-slippery surface and their colour is more or less intensified. The surface is closed and penetration of dirt is prevented.	
Application Area:	AKEMI <sup>®</sup> Stone Polish - wax based is suited for the care of fine-ground, polished, absorbent and non-absorbent natural and artificial stone, s. a. marble, granite, travertine, cotto and brick tiles, terrazzo for indoor use. In case of porous, absorbent surfaces it is necessary to apply the product several times in order to achieve brilliance.	
Instructions for Use:	<ol> <li>allow to dry.</li> <li>Apply a thin layer with a mop. Dilute with water i absorbent surfaces.</li> <li>Ideal condition to be po Polish with a soft cloth of Polish with a soft cloth of A. If necessary, repeat app 5. To achieve a good resist days.</li> <li>For regular cleaning use 7. After having cleaned app and the second seco</li></ol>	blication. stance, do not clean treated areas for 1 to 2 e AKEMI <sup>®</sup> Mild Stone Soap. prox. four times with AKEMI <sup>®</sup> Mild Stone e Polish for refreshing the surface. Add 1 to
Special Notes:	<ul> <li>AKEMI<sup>®</sup> Wax Stripper.</li> <li>For proper waste dispose emptied.</li> </ul>	Polish - wax based can be removed by sal, the container must be completely e with the guidelines of EU Decision 97/129 irective 94/62/EC.
Technical Data:	Coverage: Colour: Density: pH value:	approx. 15 - 30 m²/liter (undiluted); depending on the surface finish milky white approx. 1.01 g/cm³ approx. 5
Storage:	If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.	
Health & Safety:	Read Safety Data Sheet before handling or using this product.	
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.	